



CR1521



CR1520

45A DP COOKER CONTROL UNIT

BS 4177

2 GANG

CR1521 with DP Switched Socket

CR1520 with DP Switched Socket complete with LED

• See page 66 for customised printing

Dimension

Height	86mm
Width	146mm
Plate Depth	9mm
Overall Depth	38mm

Back Box

Surface Moulded	9054
Flush Galvanised	SB628
Dry Lining	SB631



CR1506



CR1506/COVER

50A FLEX OUTLET / COOKER CONNECTION UNIT

BS 5733

1 GANG

CR1506 with Safety Cover

50A FLEX OUTLET / COOKER CONNECTION UNIT SPARE SAFETY COVER

BS 5733 where applicable

1 GANG


CR1506/COVER Cover

Dimension

Height	86mm
Width	86mm
Plate Depth	9mm
Overall Depth	
(including outlet)	42mm

Back Box

Surface Moulded	9041
Flush Galvanised	SB618
Dry Lining	SB632



CR1400



2402/E

SHAVER SOCKET

BS EN 61558-2-5

2 GANG

CR1400 Dual Voltage 115/240V

LIGHT AND SHAVER UNIT

BS EN 61558-2-5, BS 4533

2402/E

Dual Voltage 115/240V with LED lamp

Dimension CR1400

Height	146mm
Width	86mm
Plate Depth	9mm
Overall Depth	51.5mm

Back Box

Surface Moulded	9053
Flush Galvanised	SB628
Dry Lining	SB631

Dimension 2402/E

Height	59mm
Width	492mm
Depth	70mm