CR2934

3 & 4 GANG GRID YOKE





CONSTRUCTION

Product Category Wiring Accessory **Product Group** Power & Control **Product Type** Grid System Rectangular Plate Shape Material Mild Steel Finish Galvanised **Mounting Type**

Flush/Surface Grid System

POWER

Current Not Applicable **Current Type** Not Applicable 50Hz Frequency Input Voltage 250V **Switched Poles** Not Applicable

Number of Rocker Switches

Number of Ways Not Applicable **Fuse Rating** Not Applicable

AESTHETICS

Plate Gang / Module Size 3 & 4 Grid Modules Plate Colour Grey

Not Applicable **Rocker Colour** Light Reflectance Value (LRV) Not Applicable Printing Text/Type Not Applicable

Status Indicator **Switched Outlets** Ν Part M Compliance Ν **Anti Microbial Properties** Ν

Key Features & Benefits Multifunctional Yoke Front Fixed & Screw Retained

TERMINAL

L & N Terminal Capacity as per BS Standard Not Applicable Earth Terminal Capacity as per BS Standard 4 x 1.0mm², 3 x 1.5mm², 1 x 2.5mm² **Number of Earth Terminals**

1 2Nm

Cable Strip Length 10mm **Screwdriver Type Required** Slotted Type Torque requirement as per BS Standard L&N Not Applicable Torque requirement as per BS Standard Earth

LOCATION

Max Ambient Operating Temp as per BS Req. Not Applicable Min Ambient Operating Temp as per BS Req. Max Altitude as per BS Requirement Not Applicable 2000m **IP Rating** Not Applicable

DIMENSIONAL / FIXING

Height 59.5mm Width 139mm Depth Overall (Inc Rocker) 17mm **Depth Interior only** Not Applicable Gross Weight 0.046kg Minimum Back Box Depth Suggested Back Box Depth Not Applicable Not Applicable **Fixing Centres** 120.6mm Minimum Access Top 100cm Minimum Access Bottom 100cm **Minimum Access Left** 100cm **Minimum Access Right** 100cm **Minimum Access Front** 100cm **Minimum Access Rear** 100cm

Flush Mounting Metal Box Not Applicable Flush Mounting Dry Lining Box Not Applicable **Surface Mounting Box** Not Applicable

STANDARDS


British Standard/s BS 5733 Other Markings/Standards CF

PACKAGING

Inner Carton Qty 10 **Customer MOQ** 10

SUSTAINABILITY

URL to technology list https://www.crabtreecommercial.co.uk/



Electrium Sales Limited A Siemens Company +44 (0) 1543 438310

Fax: +44 (0) 1543 000000 Email: crabtree.technical@electrium.co.uk

www.electrium.co.uk

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication, specifications and performance data are constantly changing. Latest details can be obtained from Crabtree



