




Surge Protection Devices



NMT2SPD3W/1



NMT2SPD/P

SURGE PROTECTION DEVICE

CAT REF	DESCRIPTION
NMT2SPD3W/1	Single Module Type 2 SPD

- Suitable for all Single Phase 3 Wire Systems TN-C-S, TN-S and TT
- Clear Indication of device status
- Fitted with remote signalling contact
- Suitable for use in Main Switch, Split Load & Hi-Integrity consumer unit configurations
- Not suitable for Dual RCD configurations

Alternative SPD products are available for Dual RCD consumer unit installations. Please contact Wylex technical for further assistance.

REPLACEMENT PLUG-IN CARTRIDGE

CAT REF	DESCRIPTION
NMT2SPD/P	Replacement Plug-in Cartridge for NMT2SPD3W/1

- Combined Metal Oxide Varistor (L1 & N) and Gas Discharge Tube (N & E)

TECHNICAL DATA

Product Standard	IEC EN 61643-11
Nominal discharge surge current (8/20) μ s	20kA
Short-circuit breaking capacity (I _{sc} cr)	25kA
Max. continuous voltage AC	275V
Max. discharge surge current (8/20) μ s	40kA
Voltage protection level	1.3 kV
Voltage protection level L-N	1.3 kV
Voltage protection level N-PE	1.3 kV
Max. conductor cross section (solid / stranded)	25mm ²
Degree of protection	IP20
Dimensions	Height 85mm x Width 18mm x Depth 70mm