



DATASHEET

PHOENIX


Phoenix LED 65W 5Ft High Output DD Dim 840

IP20 Traditional LED Batten Fitting
Full Range Of Attachments
Direct Replacement For Traditional Battens



GENERAL INFORMATION	
Product Code	NPH65/LED/DD/840
Product Range	Surface Mount
Product Category	Surface Mount
IP Rating	20
IK Rating	N/A
Warranty	5 Years Unlimited
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=N/A, H=N/A
Dimensions Square/Rectangular (L x W x H) (mm)	L=1527, W=61, H=64
Cut-out Size (mm)	N/A
Product Weight (Kg)	2.12
CONSTRUCTION	
Body Material	Steel Body
Body Colour	White
Optical Material	PC
Optical Finish	N/A
Termination	3x2x2.5mm sq. Push In Terminal
Driver - Intergal or Remote	Integral
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight inc. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	N/A
Luminaire Lumens (lm)	N/A
Power Consumption (W)	65
Efficacy	127
Operating Temp. (Min/Max)	-20°C to - 25°C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	4000
Correlated Rendering Index (CRI)	>80
Lumen Depreciation	L80 100000
SDCM	<3
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50
In Rush	24.9A @ 215us
Drivers per MCB*	B10=15 B16=24 C10=25 C16=40
Class	Class 1
Power Factor	>0.95
Cable Entry	Ends / Back
ELECTRICAL OUTPUT	
Forward Current (mA)	1440
Forward Voltage (Vf)	41
EMERGENCY DATA	
Mode of Operation	N/A
Battery Duration	N/A
Battery Type	N/A
Battery Specification	N/A
Ballast Lumen Factor (BLF)	N/A
DIMMING	
DALI	Yes
OTHER	N/A
Switch Dim	Yes
Corridor Function	Yes
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	5055943067097



* GUIDE ONLY

