

NVC Lighting Limited
NVC Park 201, Hollymoor Way, Rubery, Birmingham,
B31 5HE UK
T +44 (0)121 457 6340 F +44 (0)121 453 1325
E sales@nvcuk.com



DATASHEET


WOODSTOCK

Woodstock 27W LED Recessed Downlight 830-840

IP40 CCT Selectable LED Recessed Downlight
Polycarbonate Opal Diffuser
Polycarbonate Opal Diffuser



GENERAL INFORMATION	
Product Code	NWK27/830-840
Product Range	Downlights
Product Category	Downlights
IP Rating	40
IK Rating	N/A
Warranty	5 Years Unlimited
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=Ø140, H=29
Dimensions Square/Rectangular (L x W x H) (mm)	L=0, W=0, H=N/A
Cut-out Size (mm)	Ø210
Product Weight (Kg)	0.9
CONSTRUCTION	
Body Material	PC / Die Cast Aluminium
Body Colour	White
Optical Material	N/A
Optical Finish	N/A
Termination	Driver Connections
Driver - Intergal or Remote	Remote
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight inc. Carton (Kg)	N/A



LUMINAIRE PERFORMANCE	
Energy Rating	N/A
Luminaire Lumens (lm)	N/A
Power Consumption (W)	27
Efficacy	99
Operating Temp. (Min/Max)	-20°C to - 25°C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	3000 / 4000
Correlated Rendering Index (CRI)	>80
Lumen Depreciation	L80 100000
SDCM	<3
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50
In Rush	16A @ 100us
Drivers per MCB*	B10=16 B16=25
Class	Class 2
Power Factor	>0.95
Cable Entry	N/A
ELECTRICAL OUTPUT	
Forward Current (mA)	N/A
Forward Voltage (Vf)	N/A
EMERGENCY DATA	
Mode of Operation	N/A
Battery Duration	N/A
Battery Type	N/A
Battery Specification	N/A
Ballast Lumen Factor (BLF)	N/A
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	5055943059368

* GUIDE ONLY

