



Ducting - Rectangular

45° Vertical Bend



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate							
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
40045	110 x 54mm	-	-	-	-	-	-	-	-	-	-	-
55645	204 x 60mm	-	-	-	-	-	-	-	-	-	-	-
Cat. No.	Product Type	H	W	D	60 l/s		120 l/s		180 l/s			
60963	220 x 90mm	110	225	115	6		27		65			
1670	225 x 25mm	-	-	-	-		-		-			
1690	300 x 25mm	-	-	-	-		-		-			

Horizontal T-Piece - Adaptor to Connect Flat Channel Ducting




Cat. No.	Product Type	Size	Resistance (Pa) at flow rate							
			8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
40080	110 x 54mm	110 x 54mm	vary on installation							
55582	204 x 60mm	204 x 60mm	vary on installation							

Cross Over Duct Connector




Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate							
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
44273	30° Drop Down Connection	120	220	210	0.2	0.5	1.7	3.6	6.0	9.1	12.4	16.6

Rectangular Wall Plate




Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate							
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
41150	154 x 154mm	154	154	-	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
58650	172 x 172mm	172	172	-	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
51150	119 x 264mm	119	264	-	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a

Flat Channel Connector



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate							
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
40200	110 x 54mm	54	114	100	<1	<1	1.1	1.4	2.2	3.4	4.8	6.4
58200	150 x 70mm	-	-	-	-	-	-	-	-	-	-	-
55200	204 x 60mm	64	212	100	<1	<1	<1	<1	<1	<1	1.2	1.5
1520	225 x 25mm	-	-	-	-	-	-	-	-	-	-	-
1530	300 x 25mm	-	-	-	-	-	-	-	-	-	-	-
Cat. No.	Product Type	H	W	D	60 l/s		120 l/s		180 l/s			
60920	220 x 90mm	95	224	52	<1		<1		<1			

Flat Channel Connector with Internal Damper



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate							
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
40270	110 x 54mm - with Damper	60	115	75	16	17.5	19.5	22	25.5	30.5	36	42

Rigid Duct Attenuator



Cat. No.	Product Type	Size	Resistance (Pa) at flow rate							
			8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
SL55105	0.6m Length	204 x 60mm	<1	<1	2.3	4.2	-	-	-	12.2
SL55100	1.0m Length	204 x 60mm	<1	<1	2.2	4.1	-	-	-	15

Insulated Rectangular Duct



Cat. No.	Product Type	Size	Resistance (Pa) at flow rate							
			8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
IJRP55150	1.5m Length	204 x 60mm	<1	<1	1.3	2.2	3.3	4.5	5.9	7.8
IJRP55020	2.0m Length	204 x 60mm	-	-	-	-	-	-	-	-
IJRP60915	1.5m Length	220 x 90mm	-	-	-	-	-	-	-	-

Insulated Vertical Bend

Cat. No.	Product Type	Size	Resistance (Pa) at flow rate							
			8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
IJBV55645	Vertical 45° Bend	204 x 60mm	0.1	0.5	1.3	2.5	4.4	6.9	10	13.3
IJBV55600	Vertical 90° Bend	204 x 60mm	1.1	2.5	5.2	9.8	16.1	24	33.6	45

Insulated Horizontal Bend



Cat. No.	Product Type	Size	Resistance (Pa) at flow rate							
			8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
IJBH55810	Horizontal 45° Bend	204 x 60mm	0.2	0.7	1.2	2.1	3.8	6.1	9.2	13
IJBH55500	Horizontal 90° Bend	204 x 60mm	0.7	1.7	4.1	8.4	13	18	25	34
Cat. No.	Product Type	Size	60 l/s		120 l/s		180 l/s			
IJBH60950	Horizontal 90° Bend	220 x 90mm	9		36		80			

Insulated T-Piece Bend



Cat. No.	Product Type	Size	Resistance (Pa) at flow rate							
			8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
IJTH55582	T-Piece	204 x 60mm	vary on installation							