



[Addressable Call Systems](#)[Addressable Call Points](#)[Quantec Addressable Call Point, Button Reset c/w](#)[Remote Socket](#)[◀ Back to Search results for "QT602" \(7 other results\)](#)

## Quantec Addressable Call Point, Button Reset c/w Remote Socket

### Part No. **QT602**

- A programmable addressable call point c/w remote jack socket for use with C-TEC's Quantec Addressable Call System.
- Includes a Call button, Reset button and red/green confidence light.
- Can make up to 5 levels of call - Standard, Ensuite, Help Required, Emergency, Presence & Attendance (dependent on configuration and ancillary devices used). Attack and Attendance calls can also be made if connected to compatible slave infrared receiver.
- Remote socket allows the connection of optional tail call leads, pressure mats, etc.
- Can be programmed to operate in a multitude of ways using a QT423 configurator.
- Connections provided for additional slave devices such as ceiling pulls, overdoor lights, slave infrared receivers and more.
- QT602M magnetic reset version also available.

Technical Specifications 	
<b>Power requirements</b>	Nominal 24V DC (from Quantec Controller/Network).
<b>Quiescent current</b>	Less than 3mA.
<b>Alarm current</b>	14mA.
<b>Indicators</b>	Red/green confidence LED.
<b>Controls</b>	Call button; Reset button. (QT602M magnetic reset version also available).
<b>Connections</b>	Net +; Net -; R; G; L+; SW; IR; SLV.
<b>Expansion connections</b>	R; G; L+; SW; IR & SLV terminals allow the connection of optional slave overdoor lights, slave call points, slave ceiling pulls and slave infrared receivers.
<b>Onboard 6.35mm Remote Jack Socket</b>	Yes - for the optional connection of tail call leads/pear pushes, pressure mats and movement detectors.
<b>Onboard Sounder</b>	No.
<b>Onboard Infrared Receiver</b>	No.
<b>Product dimensions (mm)</b>	86 W x 86 H x 30 D mm. Can be mounted on a standard UK 25mm single gang flush or surface back box.
<b>Construction &amp; finish</b>	Plastic.
<b>IP Rating</b>	IP20.
<b>Weight</b>	72g.
<b>Operating conditions/temperature</b>	-5°C to +40°C. Max relative humidity: 95%.

Dimensions & Mounting Information 	
<b>Product dimensions:</b>	87 W x 87 H x 35 D mm. Can be mounted on a standard UK 25mm single gang flush or surface back box.

BIM/CAD Drawings▼

Documentation▼

9 other products in the same category:▼

---

## CONTACT US

 C-TEC , Challenge Way, Wigan, WN5 0LD, UK Opening times: 08:30 - 17:00 GMT.

 **+44 (0) 1942 322744**

 [sales@c-tec.co.uk](mailto:sales@c-tec.co.uk)

 [Download map](#)