

Slimline

Connection Units

- Lockable fuse carrier for safety isolation
- Clear terminal markings
- Colour coded terminals
- Neon versions available
- Neon leads enclosed
- Captive fuse carrier
- Front or bottom flex outlet versions available
- 2 earth terminals
- Captive and backed out terminals
- Terminals have large lead-ins
- In compliance with BS 1363: Part 4 as applicable
- 25-year guarantee

13 Amp Unswitched

- S1360 Unswitched spur
 S1361 Unswitched spur with neon
 S1362 Unswitched spur with front flex outlet
 S1363 Unswitched spur with neon and front flex outlet
 S1364 Unswitched spur with bottom flex outlet



S1360

S1361

S1362

13 Amp Switched

- S1370 Switched spur
 S1371 Switched spur with neon
 S1372 Switched spur with flex outlet
 S1373 Switched spur with neon and flex outlet
 S1374 Switched spur with bottom flex outlet



S1370

S1371

S1372

3 Amp Unswitched

- S1380* Unswitched spur - 3A fuse
 S1381* Unswitched spur with neon - 3A fuse



S1363

S1364

S1373

S1374

S1380

S1381

Back Boxes

minimum recommended depth

	flush 25mm	dry lining 35mm	surface 25mm
1g	DB162	DB2540	V1221

*Special order product, minimum order quantity and lead time applies