

Dimmer Switches

1 GANG SINGLE
TWO WAY 100–
1000W 50HZ
FLUSH



Blank Plates

1 GANG
FLUSH



2 GANG
FLUSH



TV/FM Coaxial Socket Outlets

NON ISOLATED
FLUSH



ISOLATED
FLUSH



FINISHES

	K1561BSS		K3330BSS		K3329BSS		K3580BSS		K3581BSS	
BRUSHED STAINLESS STEEL		1		10		5		5		5
	K1561BRC		K3330BRC		K3329BRC		K3580BRC		K3581BRC	
BRUSHED CHROME		1		10		5		5		5
	K1561SAG		K3330SAG		K3329SAG		K3580SAG		K3581SAG	
SATIN GOLD		1		10		5		5		5
	K1561PCR		K3330PCR		K3329PCR		K3580PCR		K3581PCR	
POLISHED CHROME		1		10		5		5		5

MOUNTING BOXES FOR DIMMERS:

FLUSH:
1 GANG: 861ZIC 25mm deep min
2 GANG: 862ZIC 25mm deep min
866ZIC: 35mm min for K1532BRCLV K1532SAGLV

DIMENSIONS:
1 GANG: 86 x 86mm
2 GANG: 86 x 146mm

FIXING CENTRES:
1 GANG: 60.3mm
2 GANG: 120.6mm

MOUNTING BOXES:

FLUSH:
1 GANG: 866ZIC
2 GANG: 886ZIC
SURFACE (BRC):
WITH KNOCKOUTS:
1 GANG: K899ALM
2 GANG: K897ALM
WITHOUT KNOCKOUTS:
1 GANG: K829ALM
2 GANG: K830ALM

DIMENSIONS:
1 GANG: 86 x 86mm
2 GANG: 86 x 146mm

FIXING CENTRES:
1 GANG: 60.3mm
BS 5733: 2010

MOUNTING BOXES:

FLUSH:
1 GANG: 866ZIC
2 GANG: 886ZIC
SURFACE (BRC):
WITH KNOCKOUTS:
1 GANG: K899ALM
2 GANG: K897ALM
WITHOUT KNOCKOUTS:
1 GANG: K829ALM
2 GANG: K830ALM

DIMENSIONS:
1 GANG: 86 x 86mm
2 GANG: 86 x 146mm

FIXING CENTRES:
1 GANG: 60.3mm
BS 5733: 2010

MOUNTING BOXES:

FLUSH: 861ZIC
SURFACE (BRC):
WITH KNOCKOUTS: K899ALM
WITHOUT KNOCKOUTS: K829ALM

K3580

Single outlet for connection to a single TV or FM co-axial aerial lead.

K3581, K3582

Provides safety isolation rated at 2000Va.c. between aerial lead and socket. Single outlet for connection to a single TV or FM co-axial aerial lead. Twin outlet with TV/