



PRW049/PRW050



PRW051



PRW052



PRW053



PRW020



PRW291



PRW023



PRW024



PRW040



PRW042



PRW660



PRW675

Fused Connection Units With Optional Flex Outlet

- PRW049** 3A Fused Connection Unit
- PRW050** 13A Fused Connection Unit
- PRW051** 13A Switched Fused Connection Unit
- PRW052** 13A Switched Fused Connection Unit With Neon
- PRW053** 13A Fused Connection Unit With Neon

Fused Control Switch Plates

- PRW290** 3A FCU With DP Switch (Linked)
- PRW291** 3A FCU With DP Switch & DP Fan Switch (Linked)

20A Control Switches with Optional Flex Outlet

- PRW022** 20A DP Switch
- PRW023** 20A DP Switch With Neon
- PRW040** 20A DP 'Water Heater' Switch
- PRW042** 20A DP 'Water Heater' Switch With Neon

Fan Isolation Switch

- PRW020** 10A 3 Pole Fan Isolation Switch
- PRW021** 10A 3 Pole Isolation Switch

Lockable Switch

- PRW660** 20A Double Pole Key Lockable Switch

Lockable Socket

- PRW675** 13A 1G DP Key Lockable Socket With Neon

Standards: BS 1363 and BS 1362 (fuse)
 Back Box Depth: 25mm Minimum Cable Size: 3 x 2.5mm² or 2 x 4mm²
 Dimensions: 1 Gang: (86mm x 86mm x 11mm)

Standards: BS EN 60669 660, 675: BS 1363-2, BS EN 60669-1
 Back Box Depth: 25mm Minimum 660, 675: 35mm Minimum Cable Size: 20A DP: 4 x 2.5mm² 10A 3P: 1 x 2.5mm² / 2 x 1.5mm²
 660, 675: 3 x 2.5mm², 2 x 4mm²
 Dimensions: 1 Gang: (86mm x 86mm x 11mm)