



MASTER PL-L 4 Pin



MASTER PL-L 40W/840/4P 1CT/25

Energy-saving compact fluorescent lamps Compact long-arc low-pressure mercury discharge lamp Envelope consists of 2 parallel fluorescent tubes

Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


General Information			
Cap base	2G11 [2G11]	Chromaticity coordinate X (nom.)	0.38
Life to 50% failures preheat (nom.)	20000 h	Chromaticity coordinate Y (nom.)	0.38
System description	High Frequency [High Frequency (HF)]	Correlated Colour Temperature (Nom)	4000 K
LSF preheat 2,000 hours rated	99 %	Luminous efficacy (rated) (nom.)	88 lm/W
LSF preheat 4,000 hours rated	99 %	Colour rendering index (nom.)	80
LSF preheat 6,000 hours rated	98 %	LLMF 2000 h Rated	95 %
LSF preheat 8,000 hours rated	97 %	LLMF 4000 h Rated	94 %
LSF preheat 16,000 hours rated	82 %	LLMF 6000 h Rated	93 %
LSF preheat 20,000 hours rated	50 %	LLMF 8000 h Rated	92 %
	Sphere	LLMF 12000 h Rated	91 %
		LLMF 16000 h Rated	90 %
		LLMF 20000 h Rated	90 %
Light Technical		Operating and Electrical	
Colour Code	840 [CCT of 4,000 K]	Power (Rated) (Nom)	40.0 W
Luminous flux (nom.)	3500 lm	Lamp current (nom.)	0.320 A
Luminous flux (rated) (nom.)	3500 lm		
Colour designation	Cool White (CW)		

MASTER PL-L 4 Pin

Temperature	
Design temperature (nom.)	30 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Cap-base information	4P
Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) content (max.)	2 mg
Mercury (Hg) content (nom.)	2.0 mg
Energy consumption kWh/1,000 hours	40 kWh
	423312

Product Data	
Full product code	871150061097340
Order product name	MASTER PL-L 40W/840/4P 1CT/25
EAN/UPC – product	8711500610973
Order code	61097340
Local order code	40PLL840
SAP numerator – quantity per pack	1
Numerator – packs per outer box	25
SAP material	927908208470
SAP net weight (piece)	134.000 g
ILCOS code	FSDH-40/40/1B-L/P-2G11


Dimensional drawing



PL-L 40W/840/4P HF

Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-L 40W/840/4P 1CT/25	39.0 mm	18.0 mm	509.2 mm	535 mm	541.6 mm

Photometric data



Lightcolour /840

Lightcolour /840

MASTER PL-L 4 Pin

