



MASTER SON PIA Plus



MASTER SON PIA Plus 70W/220 I E27 1CT/24

High Pressure Sodium lamp with opalized ovoid outer bulb, high output and long reliable lifetime

Warnings and Safety

- Control gear must include end-of-life protection (IEC60662, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap base	E27 [E27]
Operating position	UNIVERSAL [Any/Universal]
Life to 5% failures (nom.)	14000 h
Life to 10% failures (nom.)	17000 h
Life to 20% failures (nom.)	22000 h
Life to 50% failures (nom.)	30000 h
System description	Internal Ignitor (I)
LSF 2000 h Rated	99 %
LSF 4000 h Rated	99 %
LSF 6000 h Rated	99 %
LSF 8000 h Rated	99 %
LSF 12000 h Rated	96 %
LSF 16000 h Rated	92 %
LSF 20000 h Rated	83 %
	Sphere

Light Technical	
Colour Code	220 [CCT of 2,000 K]
Luminous flux (nom.)	5750 lm
Luminous flux (rated) (min.)	5040 lm
Luminous flux (rated) (nom.)	5600 lm
Chromaticity coordinate X (nom.)	0.54
Chromaticity coordinate Y (nom.)	0.42
Correlated Colour Temperature (Nom)	1900 K
Luminous efficacy (rated) (nom.)	80 lm/W
Color rendering index (max.)	25
Colour rendering index (nom.)	-
LLMF 2000 h Rated	92 %
LLMF 4000 h Rated	90 %
LLMF 6000 h Rated	89 %
LLMF 8000 h Rated	88 %
LLMF 12000 h Rated	87 %
LLMF 16000 h Rated	86 %

MASTER SON PIA Plus

LLMF 20000 h Rated	86 %
--------------------	------

Operating and Electrical

Power (Rated) (Nom)	71.5 W
Lamp current (EM) (nom.)	0.980 A
Ignition supply voltage (max.)	198 V
Ignition peak voltage (max.)	1800 V
Re-ignition time (min.) (max.)	600 s
Ignition time (max.)	60 s
Voltage (Max)	105 V
Voltage (Min)	77 V
Voltage (Nom)	92 V

Controls and Dimming

Dimmable	Yes
Run-up time 90% (max.)	5 min

Mechanical and Housing

Lamp Finish	Coated glass
Bulb shape	B70 [B 70mm]

Approval and Application

Energy Efficiency Class	G
-------------------------	---

Mercury (Hg) content (max.)	16.3 mg
Mercury (Hg) content (nom.)	16.3 mg
Energy consumption kWh/1,000 hours	72 kWh
	473371


Luminaire Design Requirements

Bulb temperature (max.)	350 °C
Cap-base temperature (max.)	200 °C

Product Data

Full product code	871150020426430
Order product name	MASTER SON PIA Plus 70W/220 I E27 1CT/24
EAN/UPC – product	8711500204264
Order code	20426430
Local order code	70SONIPLUS
SAP numerator – quantity per pack	1
Numerator – packs per outer box	24
SAP material	928150008835
SAP net weight (piece)	0.062 kg
ILCOS code	SE-70-H/I-E27

Dimensional drawing




SON PIA Plus 70W/220 I E27


Product	D (max)	C (max)
MASTER SON PIA Plus 70W/220 I E27 1CT/24	70 mm	152 mm

MASTER SON PIA Plus

Photometric data




LDLD_SON-PIA_0002-Light distribution diagram




LDPO_SON-PIA_0003-Spectral power distribution Colour

Lifetime



LDLE_SON-PIA_Plus_70W_I-Life expectancy diagram



LDLM_SON-PIA_Plus_70W_I-Lumen maintenance diagram

