



MASTER PL-T TOP 4 Pin



MASTER PL-T TOP 57W/840/4P 1CT/5X10CC

Energy saving compact fluorescent lamp
Compact long-arc low-pressure mercury discharge lamp
Envelope consists of 6 parallel narrow fluorescent tubes
Amalgam controlled operation

Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Product data

General Information			
Cap base	GX24Q-5 [GX24q-5]	Chromaticity coordinate X (nom.)	0.38
Life to 50% failures preheat (nom.)	13000 h	Chromaticity coordinate Y (nom.)	0.38
LSF preheat 2,000 hours rated	99 %	Correlated Colour Temperature (Nom)	4000 K
LSF preheat 4,000 hours rated	98 %	Luminous efficacy (rated) (min.)	76 lm/W
LSF preheat 6,000 hours rated	97 %	Colour rendering index (nom.)	80
LSF preheat 8,000 hours rated	90 %	LLMF 2000 h Rated	92 %
	Sphere	LLMF 4000 h Rated	88 %
		LLMF 6000 h Rated	85 %
		LLMF 8000 h Rated	84 %
		LLMF 12000 h Rated	81 %
Light Technical		Operating and Electrical	
Colour Code	840 [CCT of 4,000 K]	Power (Rated) (Nom)	57.0 W
Luminous flux (nom.)	4000 lm		
Luminous flux (rated) (nom.)	3900 lm		
Colour designation	Cool White (CW)		

MASTER PL-T TOP 4 Pin


Lamp current (nom.)	0.320 A
Temperature	
Design temperature (nom.)	28 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Cap-base information	4P
Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) content (max.)	1.4 mg
Mercury (Hg) content (nom.)	1.4 mg
Energy consumption kWh/1,000 hours	57 kWh

Dimensional drawing



PL-T TOP 57W/840/4P A


Photometric data



Lightcolour /840

	423334
Product Data	
Full product code	871150061034870
Order product name	MASTER PL-T TOP 57W/840/4P 1CT/5X10BOX
EAN/UPC – product	8711500610348
Order code	61034870
Local order code	57PLT8404PINTOP
SAP numerator – quantity per pack	1
Numerator – packs per outer box	50
SAP material	927912484069
SAP net weight (piece)	101.000 g
ILCOS code	FSM6H-57/40/1B-L/P-GX24q=5



Product	D (max)	A (max)	B (max)	C (max)
MASTER PL-T TOP 57W/840/4P 1CT/5X10BOX	41 mm	157.7 mm	182.0 mm	197.7 mm



Lightcolour /840


MASTER PL-T TOP 4 Pin

Lifetime



LDLM_PLTTOP4P_0001-Lumen maintenance diagram

LDLE_PLTTOP4P_0001-Life expectancy diagram



LDLE_PLTTOP4P_0002-Life expectancy diagram

