



RFDEL-71B



RFDA-71B



RFDAC-71B



RFSA-61F *flow*

RFDEL-71F *flow*

Receivers

RFDEL-71B

160Va LED Dimming Receiver c/w Control Input

Offers leading and trailing edge technology with trim facility. Compatible with most dimmable LED light sources. Can utilise retractive switches in conjunction with the 230V ~ switch input.

RFDA-71B

250W Resistive/Inductive Dimming Receiver

RFDAC-71B

0(1)-10V Analogue Dimming Receiver

0(1)-10V 1 Channel Multifunction Dimming Receiver. Complete with 230V ~ 16A ON/OFF Switch Control

Receivers

RFSA-61F

16A Switching Receiver (Flow™ Enclosure)

RFDEL-71F

160Va LED Dimming Receiver (Flow™ Enclosure)

Offers leading and trailing edge technology with trim facility. Compatible with most dimmable LED light sources.

Standards: EN 60669, EN 300220, EN 301489

Cable Length: RFDEL-71B, RFDAC-71B, RFDA-71B: 90mm

Dimensions: RFDEL-71B, RFDAC-71B, RFDA-71B: 49mm x 49mm x 21mm, RFSA-61F, RFDEL-71F: 260mm x 52mm x 25mm



From our family to yours...



Join our Smart family at click-smart.com to learn more about how Click Smart can upgrade your home and make your own lifestyle smarter.

In a series of entertaining, easy to follow videos our family demonstrate how the Click Smart range can eliminate the everyday annoyances and enhance your home environment.

click-smart.com