

- High mechanical strength
- IP rating: IP66 + IP67 + IP68 (5 bar) + IP69
- Temperature range **(-50°C to +135°C)**
(-60°C to +85°C EXD)
- Oil resistant
- UV resistant
- Nickel Plated Brass Fittings

- Earthing ferrule is manufactured in machined Nickel Plated Brass to facilitate easy assembly and re-use
- Stainless steel fittings also available contact us
- Metric threads supplied with Insulated Throats
- Swivel fittings allows the thread to swivel about the main body even after tightening

- Vibration and shock tested to EN61373 Cat 2
- Conforms to EN 61386
- Interchangeable with all Liquid tight conduits made to American (UL360) sizes
- For other Liquid tight conduits please refer to www.flexicon.uk.com
- For more details on LTP EXD fitting refer to www.flexicon.uk.com

NEW

C-SF - swivel internal thread nickel plated brass

Multi part compression fitting including elastomeric seal. Swivel internal thread makes it suitable for connection to male threads. Internal thread swivels about the main body even after tightening.

IP66 IP67 IP68 IP69



metric thread
part number

LTP16-M20-SF
LTP20-M20-SF
LTP25-M25-SF

C90 - external thread nickel plated brass

90° multipart compression fitting including elastomeric seal. Can be used for knockouts.

IP66 IP67 IP68 IP69



metric thread
part number

LTP16-M16-C90
LTP16-M20-C90
LTP20-M20-C90
LTP25-M25-C90
LTP32-M32-C90

C45 - external thread nickel plated brass

45° multipart compression fitting including elastomeric seal. Can be used for knockouts.

IP66 IP67 IP68 IP69



metric thread
part number

LTP16-M20-C45
LTP20-M20-C45
LTP25-M25-C45
LTP32-M32-C45

Coupler - nickel plated brass

Multi part compression coupler including elastomeric seals to connect with an external thread.

IP66 IP67 IP68 IP69



part number

LTP16-LTP16
LTP20-LTP20
LTP25-LTP25
LTP32-LTP32

FW - fibre, retained face sealing washers

Retained sealing washer to maintain IP rating of fitting to adjacent equipment.



metric thread
part number

FW16
FW20
FW25
FW32

LTP-EXD

Nickel Plated Brass gland with a nylon and elastomeric seal and two part epoxy resin pack. Supplied in boxes of one, complete with instructions and gloves.

Visit website for more details.

APR Cert No.2624

IP66 IP67 IP68 IP69



metric thread
part number

LTP16-M20-EXD
LTP20-M20-EXD
LTP25-M25-EXD
LTP32-M32-EXD