

Product Code: CT1400

Description: 20A 4 Pole Flow™ Ceiling Rose (Without Cover)



General Information

Dimensions	85mm Diameter x 35mm
Material Composition	Cover: Polycarbonate Base & Terminal Housing: Nylon (PA66) Terminals: Silver Plated Brass Terminal Screws: Steel and Yellow Passivated
Maximum Voltage	250V~ 50Hz
Load Rating	20A
Rated Impulse Voltage	4kV
Terminal Capacity	3 x 2.5mm ² Max. T&E, 3 x 1.5mm ² Max. Flex
Termination Layout	L - E - N - A
Inner Core Strip Length	L & N: 35mm; E: 43mm
Conductor Strip Length	10mm
Ingress Protection	IP20
Operational Temperature	-5°C to +40°C
Warranty	10 Years

Connector Information	Compatible Connectors (Without CT1401 Cover): All 3 Pole & 4 Pole Male Connectors Compatible Connectors (With CT1401 Cover): CT101C, CT102C & CT202C (Male Connectors) Conduit Installations: Suitable For Installation On To Conduit (BESA) Boxes
------------------------------	--

Standards	EN 61535: 2009 EN 61535: 2009 + A1: 2013 BS 5733: 2010 + A1: 2014 BS 8488 : 2009+ A1 :2010
------------------	---



Additional Information	Ensure that the mains supply is isolated before commencing installation. Always refer to the circuit diagram supplied with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Pre-fabricating wiring systems manufactured to BS 8488 by other manufacturers may not be compatible or safely inter-connectable with this system. Any dangerous compatibility between different manufactures installation coupler systems is not automatically prevented by compliance with IEC 61535.
-------------------------------	--