

Product datasheet

Specifications



LOAD CTR 240/415 V 3 PH 4 W 125 A 24 SPACES

KQ24B125

KQ24B125 has not been replaced. Please contact your customer care centre for more information.

⚠ Discontinued

Main

Range	Acti 9
Product name	Load centre KQ II B
Product or component type	Distribution board
Device application	Distribution
Enclosure type	Standard
Door type	Overall
Provided equipment	Enclosure Door Front cover Pan assembly Earth terminal block 25 mm² Shielded neutral bar 25 mm²

Complementary

Enclosure mounting	Surface
[Ie] rated operational current	125 A at 400/415 V AC
Incomer device options	Lugs Switch disconnector - 4P Terminal block - 4P MCCB - 4P RCCB - 30 mA - 4P RCCB - 100 mA - 4P RCCB - 300 mA - 4P
Protection device options	Miniature circuit breaker (MCB) (plug-on type) as outgoer Residual current circuit breaker with overcurrent protection (RCBO) (plug-on type) as outgoer
Number of ways	8 ways (3P) outgoer
Cable entry	top and bottom: knock-out side: knock-out
Height	538 mm
Width	470 mm
Depth	139 mm

Environment

IP degree of protection	IP2x B internal conforming to BS EN 60529 IP3x external conforming to BS EN 60529
-------------------------	--

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Package 1 Weight	12473.790 g
------------------	-------------

Contractual warranty

Warranty	18 months
----------	-----------