

MASTER LEDbulb



MASTER LEDbulb DT 5.5-40W E27 A60 CL

MASTER LEDbulb range delivers a dimmable glow effect for a welcoming, warm atmosphere, making it ideal for general lighting applications in the hospitality industry. Its unique design radiates warm light in all directions, making it a true alternative to the incandescent lamp. It is particularly suitable for public areas such as lobbies, corridors, stairwells, where the light is always on.;Compatible with existing fixtures with an E27 or a B22 holder and designed for retrofit replacement of incandescent bulbs, MASTER LEDbulb delivers huge energy savings and minimises maintenance cost without any compromise on light quality.

Warnings and Safety

- \cdot Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- $\boldsymbol{\cdot}$ Not intended for use with emergency light fixtures or exit lights

Product data

General information	
Cap base	E27 [E27]
EU RoHS compliant	Yes
Nominal lifetime (nom.)	25000 h
Switching cycle	50,000X
	Sphere
Light technical	
Colour Code	822-827 [tunable warm white]
Luminous flux (nom.)	470 lm
Colour designation	Warm Glow (WG)
Correlated Colour Temperature (Nom)	2200 2700 K
Luminous efficacy (rated) (nom.)	85.00 lm/W

Colour consistency	<6
Colour rendering index (nom.)	80
LLMF at end of nominal lifetime (nom.)	70 %
Operating and electrical	
Input frequency	50 to 60 Hz
Power (Rated) (Nom)	5.5 W
Lamp current (nom.)	26 mA
Wattage equivalent	40 W
Starting time (nom.)	0.5 s
Warm-up time to 60% light (nom.)	0.5 s
Power factor (nom.)	0.9


Datasheet, 2022, July 28 data subject to change

MASTER LEDbulb

Voltage (Nom)	220-240 V
Temperature	
T-Case maximum (nom.)	80 ℃
Controls and dimming	
Dimmable	Only with specific dimmers
Mechanical and housing	
Lamp Finish	Clear
Bulb shape	A60 [A 60mm]
Approval and application	
Energy Efficiency Class	F

Energy consumption kWh/1,000 hours	6 kWh
	614852
Product data	
Full product code	871951430630100
Order product name	MASTER LEDbulb DT 5.5-40W E27 A60 CL
EAN/UPC – product	8719514306301
Order code	30630100
SAP numerator – quantity per pack	1
Numerator – packs per outer box	10
SAP material	929002490002
Copy Net Weight (Piece)	0.076 kg


Dimensional drawing



MASTER LEDbulb DT 5.5-40W E27 A60 CL


Product D C MASTER LEDbulb DT 5.5-40W E27 A60 CL 60.5 mm 109 mm

Photometric data



Calculus Photometrics 43 Philips Lighting B.V. Pages 17


LEDbulb MAS SLR1 5,5W A60 E27 827 CL-GUL



LEDbulb MAS SLR1 A60 5,5W E27 827 CL-LDD


MASTER LEDbulb


Photometric data



LEDbulb MAS SLR1 5,5W A60 E27 827 CL-POC

Lifetime





Life Expectancy Diagram

Lumen Maintenance Diagram



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.