

Electric Showers

T80 Family

Triton's T80 family of electric showers has been an iconic household favourite for more than 30 years and includes Britain's most popular shower; the T80z Fast Fit. Packed with design features that will appeal to both the homeowner and the professional installer, T80 showers feature the latest Swing-Fit™ and Swivel-Fit™ installation technology as well as delivering Triton style, quality and showering performance. A T80 shower makes it easy to create your perfect shower first time - both you and your installer will love it.



Ease of Installation



See page 51 for more information on ease of installation.

T80 Pro-Fit Electric Shower

A brilliantly finished model which can be easily fitted from left or right, the highly durable Triton Pro-Fit is suitable for copper or plastic fittings, as a compression or push fit. Boasting Dura-Flow™ technology for a longer lasting shower, plus fully adjustable riser rail and extended anti-twist hose for added flexibility, it's an electric shower as easy to use as it is to connect.

- 8 water and 8 cable entry points
- Makes it easy to replace any existing models
- Easy to use controls for both flow and temperature
- 5 mode Dura-Flow™ shower head that is easy to clean

T80 Pro-Fit Eco

The eco model is all about being green. Cutting water usage down by up to 50%, it's great for the environment, and your wallet, too!


Ref: SP8007PF - 7.5kW
SP8008PF - 8.5kW
SP8009PF - 9.5kW
SP8001PF - 10.5kW
ECO8008PF - Eco 8.5kW



Amore

electric shower
8.5kW, 9.5kW (240v)

Temperature Control	Stabilised
Power Ratings	8.5kW, 9.5kW (240v)
Inlet Connection	15mm male compression
Water Entry Points	Top, bottom, side bottom, back (left hand side unit) Bottom, side bottom, back (right hand side unit)
Cable Entry Points	Top, bottom, side bottom, back (left hand side unit)
Outlet Connection	½" BSP
Plumbing System	Cold mains only
Minimum Running Pressure/Flow	1 Bar @ 8 l/min
Maximum Static Pressure	10 Bar
Surface Mounted Only	
Approvals, Complies with	BEAB, CE, BSI Kitemark, WRAS
Guarantee	2 years




Finish	Power	Code
Gloss Black	8.5kW	ASPAM08GSLBK
Gloss Black	9.5kW	ASPAM09GSLBK
Gloss White	8.5kW	ASPAM08GSWHT
Gloss White	9.5kW	ASPAM09GSWHT
Brushed Steel	8.5kW	ASPAM08BRSTL
Brushed Steel	9.5kW	ASPAM09BRSTL

To see all finishes and for further details please see page 26

Touch

electric shower
8.5kW and 9.5kW (240v)

Temperature Control	Stabilised
Power Ratings	8.5kW, 9.5kW (240v)
Inlet Connection	15mm compression
Water Entry Points	Top, bottom, back (left hand side unit) Bottom, back (right hand side unit)
Cable Entry Points	Top, bottom, back (left hand side unit) Bottom (right hand side unit)
Outlet Connection	½" BSP
Plumbing System	Cold water only
Minimum Running Pressure/Flow	1 Bar @ 8 l/min
Maximum Static Pressure	10 Bar
Surface Mounted Only	
Approvals, Complies with	BEAB, CE, BSI Kitemark
Guarantee	2 years




Finish	Power	Code
White	8.5kW	ASPTOU08WHT
White	9.5kW	ASPTOU09WHT

T300si

remote electric shower
8.5kW, 9.5kW and 10.5kW (240v)

Temperature Control	Stabilised
Power Ratings	8.5kW, 9.5kW, 10.5kW (240v)
Inlet Connection	15mm compression
Water Entry Points	Bottom, back (right hand side unit)
Cable Entry Points	Top, back (right hand side unit)
Outlet Connection	½" BSP
Plumbing System	Cold water only
Minimum Running Pressure/Flow	1 Bar @ 8 l/min and 1.5 Bar @ 11 l/min for 10.5kW
Maximum Static Pressure	10 Bar
Surface Mounted Only	
Approvals, Complies with	BEAB, CE, BSI Kitemark
Guarantee	2 years




Finish	Power	Code
White/Chrome	8.5kW	ASP3008SI
White/Chrome	9.5kW	ASP3009SI
White/Chrome	10.5kW	ASP3001SI

Aspirante Wireless

remote electric shower
8.5kW, 9.5kW and 10.5kW (240v)

Temperature Control	Stabilised
Power Ratings	8.5kW, 9.5kW, 10.5kW (240v)
Inlet Connection	15mm compression
Water Entry Points	Bottom, back (right hand side of unit)
Cable Entry Points	Back, top (right hand side of unit)
Outlet Connection	1/2" BSP
Plumbing System	Cold water only
Minimum Running Pressure/Flow	1 Bar @ 8 l/min and 1.5 Bar @ 11 l/min for 10.5kW
Maximum Static Pressure	10 Bar
Surface Mounted Only	
Approvals, Complies with	BEAB, CE, BSI Kitemark
Guarantee	2 years




Finish	Power	Code
Chrome	8.5kW	SP3008SI
Chrome	9.5kW	SP3009SI
Chrome	10.5kW	SP3001SI

T80 Pro-Fit

electric shower
7.5kW, 8.5kW, 9.5kW and 10.5kW (240v)

Temperature Control	Stabilised
Power Ratings	7.5kW, 8.5kW, 9.5kW, 10.5kW (240v)
Inlet Connection	15mm compression
Water Entry Points	Top, bottom, side bottom, back (left hand side unit) Top, bottom, side bottom, back (right hand side unit)
Cable Entry Points	Top, bottom, side bottom, back (left hand side unit) Top, bottom, side bottom, back (right hand side unit)
Outlet Connection	½" BSP
Plumbing System	Cold water only
Minimum Running Pressure/Flow for full performance*	1 bar at 8 l/min 1.5 bar at 11 l/min for 10.5kW*
Maximum Static Pressure	10 Bar
Surface Mounted Only	
Approvals, Complies with	BEAB, CE, BSI Kitemark, WRAS
Guarantee	2 years



Finish	Power	Code
White	7.5kW	SP8007PF
White	8.5kW	SP8008PF
White	9.5kW	SP8009PF
White	10.5kW	SP8001PF
White	8.5kW	ECO8008PF


To see all finishes and for further details please see page 30

*At running pressure/flow 0.7 Bar at 8 l/min (1.2 Bar at 11 l/min for 10.5kW) the shower will continue to operate at a reduced performance.

T80Z Fast-Fit

electric shower
7.5kW, 8.5kW, 9.5kW and 10.5kW (240v)

Temperature Control	Stabilised
Power Ratings	7.5kW, 8.5kW, 9.5kW, 10.5kW (240v)
Inlet Connection	15mm compression
Water Entry Points	Top, bottom, side bottom, back (left hand side unit) Top, bottom, side bottom, back (right hand side unit)
Cable Entry Points	Top, bottom, back (left hand side unit) Top, bottom, back (right hand side unit)
Outlet Connection	½" BSP
Plumbing System	Cold water only
Minimum Running Pressure/Flow for full performance*	1 bar at 8 l/min 1.5 bar at 11 l/min for 10.5kW*
Maximum Static Pressure	10 Bar
Surface Mounted Only	
Approvals, Complies with	BEAB, CE, BSI Kitemark
Guarantee	2 years




Finish	Power	Code
Chrome	8.5kW	SP8CHR8ZFF
Chrome	9.5kW	SP8CHR9ZFF
Chrome	10.5kW	SP8CHR1ZFF
White/Chrome	7.5kW	SP8007ZFF
White/Chrome	8.5kW	SP8008ZFF
White/Chrome	9.5kW	SP8009ZFF
White/Chrome	10.5kW	SP8001ZFF
White/Chrome	8.5kW	ECO8008ZFF

*At running pressure/flow 0.7 Bar at 8 l/min (1.2 Bar at 11 l/min for 10.5kW) the shower will continue to operate at a reduced performance.

T80Z Thermostatic Fast-Fit

electric shower
8.5kW, 9.5kW & 10.5kW (240v)

Temperature Control	Thermostatic
Power Ratings	8.5kW, 9.5kW, 10.5kW
Inlet Connection	15mm compression
Water Entry Points	Top, bottom, side bottom, back (left hand side of unit) Top, bottom, side bottom, back (right hand side of unit)
Cable Entry Points	Top, bottom, back (left hand side of unit) Top, bottom, back (right hand side of unit)
Outlet Connection	½" BSP
Plumbing System	Cold water only
Minimum Running Pressure/Flow for full performance*	1.0 Bar @ 8 l/min 1.5 Bar @ 11 l/min for 10.5kW
Maximum Static Pressure	10 Bar
Surface Mounted Only	
Approvals, Complies with	BEAB, CE, BSI Kitemark
Guarantee	2 years



Finish	Power	Code
White/Chrome	8.5kW	SP8008ZFFTHM
White/Chrome	9.5kW	SP8009ZFFTHM
White/Chrome	10.5kW	SP8001ZFFTHM


For further details please see page 31

*At running pressure/flow 0.7 Bar at 8 l/min (1.2 Bar at 11 l/min for 10.5kW) the shower will continue to operate at a reduced performance.

T80si Pumped

electric pumped shower
8.5kW & 9.5kW

Temperature Control	Stabilised
Power Ratings	8.5kW, 9.5kW
Inlet Connection	15mm push fit
Water Entry Points	Top, bottom, back (left hand side of unit)
Cable Entry Points	Top, bottom, back (left hand side of unit)
Outlet Connection	½" BSP
Plumbing System	Cold water cistern only
Minimum Running Pressure/Flow for full performance*	80mm @ 8 l/min
Maximum Static Pressure	10m
Surface Mounted Only	
Approvals, Complies with	BEAB, CE, BSI Kitemark
Guarantee	1 years



Finish	Power	Code
White/Chrome	8.5kW	SP8P08SI
White/Chrome	9.5kW	SP8P09SI