

**LAMPS**

LED

6-8W

STANDARDS

IP65 IK03

ORDERING GUIDE

Legend kits (ISO/BSEN) to be ordered separately.

Description	SAP Code	Cat. No.
Voyager Solid		
VOYAGER SOLID L MS E3D-S WH	96629766	VYSOLE3D
VOYAGER SOLID L MS E3-S WH	96629764	VYSOLE3
VOYAGER SOLID L MS E3T-S WH	96629765	VYSOLE3T
VOYAGER SOLID MS E3D-S WH	96629763	VYSOE3D
VOYAGER SOLID MS E3-S WH	96629761	VYSOE3
VOYAGER SOLID MS E3T-S WH	96629762	VYSOE3T
Voyager Solid Legends		
VOYAGER SOLID L LEGENDSET SM-1S	96629768	VYSOLEGG
VOYAGER SOLID LEGENDSET SM-1S	96629767	VYSOLEGG
Voyager Solid Accessories		
VOYAGER SOLID FSR WH	96629769	
VOYAGER SOLID L FSR WH	96629770	
Voyager Solid Spares		
VOYAGER SOLID ACCU NICD 1,5AH (FOR DALI)	59009286	
VOYAGER SOLID ACCU NIMH 2,2AH	59009287	

To make reading our ordering guides easier please use the SAP description key fold out, inside the back cover. For more information please visit our website www.thornlighting.com and simply search for our products.

SOLID WITHOUT OPAL INLET

h	antipanic (0,5 lx)		escape (1 lx)	
	a1	a2	a1	a2
2.50	2.65	8.00	2.90	7.50
3.00	2.75	8.75	2.95	7.95
3.50	2.85	9.25	2.90	8.25
4.00	2.95	9.75	2.80	8.35
4.50	2.90	10.15	2.60	8.35
5.00	2.90	10.50	2.20	8.20

SOLID L WITHOUT OPAL INLET

h	antipanic (0,5 lx)		escape (1 lx)	
	a1	a2	a1	a2
2.50	2.00	11.35	-	5.75
3.00	1.05	11.75	-	3.10
3.50	-	11.00	-	-
4.00	-	10.10	-	-
4.50	-	8.85	-	-
5.00	-	7.50	-	-

Key

h - height of the room

a1- distance of the luminaire to the wall


a2 - distance from luminaire to luminaire

All values in metres


All values for ta - 30°C

Maintenance factor - 0.8

Values for E3D Version



Voyager Solid



Voyager Solid L

