

96628879 COLLEGE LED6500-840 HF E3 L1500

LED 64W LED_CLLG_6500	IP44	IK05			850°C	T _a -10 +25	
-----------------------	------	------	---	---	-------	---------------------------	--

College

A high performance, surface mounted, LED luminaire. Electronic, fixed output control gear with 3 hour, manual test, emergency lighting circuit. Class I electrical, IP44. Body: white painted steel. End caps: white polycarbonate with a curved, precision extruded clear prismatic polycarbonate diffuser. Ø21.5mm cable entry hole in the centre of the back spine with optional cable entry through each end cap. Fitting supplied with sealing grommets and innovative "quick fix" horseshoe and sliding washers for direct screw fixing to surface, fixing centres 1450mm. Standard BESA fixings. Can be suspended using wire suspension accessory kit (to be ordered separately). 4 x 2 x 2.5mm² piano key terminal block. Complete with 4000K LED


Dimensions: 1520 x 217 x 90 mm

Total power: 64 W


Weight: 4.9 kg



TLG_CLLG_F_P1.jpg



TLG_CLLG_M_LD1.wmf



TLG_SP_0043019.idt

Lamp position: STD - standard

Light Source: LED

Luminaire luminous flux*: 6500 lm

Total emergency luminous flux: 300 lm

Luminaire efficacy*: 102 lm/W

Lamp efficacy: 101 lm/W

Colour Rendering Index min.: 80

Correlated colour temperature*: 4000 Kelvin

Chromaticity tolerance (initial MacAdam)*: 3

Rated median useful life*:

50000h L80 at 25°C

Ballast: 1x HF_Xitanium

Luminaire input power*: 64 W

Charging power: 4 W

Dimming: FO

Maintenance category: D - Enclosed IP2X


LOR: 1,00 ULOR: 0,05 DLOR: 0,95

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Colour temperature is subject to a tolerance of up to ± 150 Kelvin from the nominal value. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

In most products the failure of one LED point causes no functional impairment to the lighting performance of the luminaire and is therefore no reason for complaint. Unless otherwise stated all Thorn LED products are suitable for unrestricted use (rated RG0 or RG1) with regard photobiological blue light safety (IEC/EN60598-1).

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.

© Thorn Lighting



Light output ratio	
LOR	100 %
ULOR	5 %
DLOR	95 %
FFR	0.05 (5:95)
BLF	1.00

Glare Evaluation	
X = 4 H, Y = 8 H	S = 1.00 H
Reflection factors	70/50/20
UGR transversal	<22
UGR axial	<19

Classification	
LiTG	A41
EN	
BZ	BZ3/1.25/BZ4
UTE	0.95 D + 0.05 T
CIE Flux Codes	52 82 95 95 100

Utilization Factors									
Room Reflectance Ceiling/Walls/Floor	Room Index								
	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
70 / 50 / 20	63	70	77	82	88	93	96	100	102
70 / 30 / 20	55	63	70	76	83	87	91	96	99
70 / 10 / 20	50	58	65	71	78	83	87	92	96
50 / 50 / 20	60	68	74	79	84	88	91	95	97
50 / 30 / 20	54	62	68	73	80	84	87	92	95
50 / 10 / 20	50	57	64	69	76	81	84	89	92
30 / 50 / 20	59	66	71	76	81	85	87	90	93
30 / 30 / 20	53	60	67	71	77	81	84	88	90
30 / 10 / 20	49	56	63	67	74	78	81	86	88
0 / 0 / 0	47	53	59	64	70	73	76	80	83
According to CIBSE Technical Memorandum No. 5 1980						SHR Nom =	1.50		
						SHR Max =	1.54		
						SHR Max TR =	1.73		

Photometric data file: TLG_SP_0043019.lgt