

Product datasheet

Specifications



Polyester glassreinforced plinth for encl. PLM86 front opening IP44-IK10 RAL7035

NSYZM263G

Main

Range	Thalassa
Accessory / separate part category	Enclosure accessory
Product or component type	Plinth
Anwendung	Multi-purpose
Nennmaße des Gehäuses	-
Device composition	fixing elements 2 front panel 2 side part
Range compatibility	Thalassa PLM

Complementary

Fixing mode	By screws - on side parts location
Colour	Plinth: grey (RAL 7035)
Height	200 mm
Width	556 mm
Depth	302 mm

Environment

IP degree of protection	IP44
IK degree of protection	IK10

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	7.15 kg
Package 1 Height	18 cm
Package 1 width	22 cm
Package 1 Length	60.5 cm

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------