

2 Year Warranty

L70 25,000hrs

On/Off, Tuneable, RGB and
Dimmable control



requires

.hub

SmartThings Hub
See pg.21




AOne™ Smart Hub
See pg.23




works with

.control

Smart Battery Dimmer
See pg.33



Kinetic Controller
See pg.37




Remote Control
See pg.39




.sense

Door/Window
Sensor
See pg.51



PIR Sensor
See pg.51



AU-A1GUZBCX5
(OD) 50mm Overall (Ø)
(L) 54mm Length

AU-A1GUZBRGBW
(OD) 50mm Overall (Ø)
(L) 61mm Length

AOne™.light

Zigbee Tuneable White & RGB + Tuneable
White GU10 Lamps



**SMART
inside**

See pg.256-258
for compatibility table

5-100% Dimming range

AU-A1GUZBCX5 - Tuneable white colour temperature between 2200-5000K

AU-A1GUZBCX5 - Suitable for use in Aurora fire rated downlights

AU-A1GUZBRGBW - RGB plus tuneable white colour between 2700-6500K

60° beam angle for uniform light distribution

Can be used in lighting scenes and within lighting schedules

Ability to be controlled individually or within a space



AOne™ Tuneable White GU10

2200K 5000K
340lm 400lm



AOne™ RGB + Tuneable White GU10

2700K 4000K 6500K
400lm 130lm 70lm
"Create millions of colours"

Cat. No.	Base	Watts	Colour	Lumens	lm/W	Beam
Tuneable White GU10						
AU-A1GUZBCX5	GU10	5.4W	2200-5000K	400lm	74	60°
RGB + Tuneable White GU10						
AU-A1GUZBRGBW	GU10	5.6W	2700-6500K	400lm	71	60°



Lumen value stated in table is based on total lumens at 5000K for Tuneable White and 2700K for RGB + Tuneable White, lumen levels on the RGB + Tuneable White drop at different CCTs