

Product datasheet

Specifications



auxiliary contact SDE low level - 1 NO/NC - for Masterpact NT

47079

Main

Device short name	SDE
Product or component type	Auxiliary contact
Device application	Connection
Range compatibility	MasterPact NT circuit breaker
Signal contacts composition	1 NO/NC

Complementary

Auxiliary contacts type	Low level
[I _e] rated operational current	DC-12: 3 A at 24/48 V DC DC-12: 0.15 A at 250 V DC DC-12: 0.3 A at 125 V DC AC-12: 3 A at 24/48 V AC 50/60 Hz AC-12: 3 A at 240 V AC 50/60 Hz AC-12: 3 A at 380 V AC 50/60 Hz
Minimum load	2 mA at 15 V
Accessory / separate part category	Spare parts for Masterpact NT

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	22 g
Package 1 Height	3 cm
Package 1 width	6 cm
Package 1 Length	12 cm
Unit Type of Package 2	S03
Number of Units in Package 2	140
Package 2 Weight	3.567 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
-----------------	-----------
