

FS1226-T BATTERY POWERED ENHANCED HEAT ALARM

| | |
|--------------|---|
| Sensor type | Thermistek |
| Battery type | 10 year sealed for life Panasonic lithium |



- **Smart RF Ready** - Fit a Smart RF Radio Module (FS1521W2) to wirelessly interlink up to 50 FireAngel Smart RF products, including FireAngel Connect Gateway.
- Connects directly to the **FireAngel Connect Gateway**, providing enhanced diagnostic capabilities and realtime notifications to mobile devices. (Requires FS1521W2 Smart RF Module)
- Thermistek technology as used by over 90% of the UK Fire and Rescue Services
- Enhanced thermal sensor predicts when the temperature will rise to a dangerous level
- Easily accessible central button - Test / Smart Silence / Locate
- Silence function - allows the alarm to be silenced in the event of a known false alarm
- Suitable to protect the most dangerous room within a home, a kitchen.
- Grade F1 as per BS 5839-6:2019

Technical Specification

| | |
|-----------------------------|--|
| Product Dimensions | 132mm (diameter) x 60mm (depth) |
| Supply voltage | 3V DC |
| Battery | 10 year sealed for life Panasonic lithium battery |
| Technology | Thermistek Enhanced Thermal Sensor and Smart RF Ready |
| Alarm sound level | 85dB(A) at 3m (minimum) |
| Installation positions | Ceiling |
| For use in: | Kitchen, Garage, Loft |
| Alarms at temperature range | +54°C to +62°C |
| Operating temperature | +4°C to +38°C |
| Operating humidity | Up to 90% RH non-condensing |
| Storage temperature | -20°C to +60°C |
| Storage humidity | Up to 93% RH non-condensing |
| Plastic material | ABS, UL94 VO fire retardant |
| Warranty | 5 years |
| Master pack quantity | 10 |
| Product Weight | 143g |
| Certified to | BS 5446-2: 2003 |
| Operating Frequency | 868 MHz |

Create a Safety Network
Add a Smart RF Radio Module to wirelessly interlink up to 50 Smart RF devices with a simple 2 step process.



Smoke Alarm



CO Alarm



Wireless Alarm Control Unit



Assisted Living Solutions

For further information or sales enquiries, contact your local Specification Manager:
www.fireangel.co.uk/specification-manager