



Easi-Mark cable markers - on reels.

Key features.

- Ideal for cables from 0.75mm² to 35.0mm²
- Supplied on reels
- Ideal for general panel building, mass transit, telecoms and utilities
- Dramatic savings on installation time particularly when used with specialist application tool
- The self-grip design reduces the chances of markers being moved when drawn into ducting or when bending conductors

Available marks.

Black on white (B/W)



Colour coded (C/C)



Specification.

Material:
Easy-to-handle soft PVC compound

Colour options:
Black on white or colour coded

Service temperature range:
-45°C to +70°C

Elongation at break:
ASTM D-638

UV-resistance:
30 days at 0,35W/m²@340nm;
black temperature: 63°C

Humidity:
30days at 37°C/95%R.H.

QUV-resistance:
ASTM G154

Part number	Cable size (mm ²)	Marker length (mm)	Cable size mm ² (with applicator)	Applicator part number	Reel quantity
0.8	7/0.2 - 16/0.2	4	0.75	EMA1	1000
2.0	Up to 0.75	3	4.0	EMA2	1000
2.5	0.5 - 1.5	4	6.0	EMA3	1000
3.5	1.5 - 4.0	4	10.0	EMA3	500
6.0	10.0 - 16.0	5	35.0	EMA4	500

01582 606033 | sales@cablecraft.co.uk | cablecraft.co.uk

Cablecraft House, Circle Business Centre, Blackburn Road, Houghton Regis, Bedfordshire, LU5 5DD

Cablecraft part of Shoal Group Limited

Shoal Group Limited | Company registration number 12772850

Registered in England and Wales at 12 Charterhouse Square, London EC1M 6AX

