



## Green/yellow PVC sleeving - coils.

### Key features.

- This high-grade PVC sleeving has a thin wall that makes it ideal for insulating wire in areas where space is premium
- Supplied in continuous 100m coils
- Some sizes are available supplied on reels, please contact us for more information

| Part number                 | Internal dia. (mm) | To cover cable size (mm <sup>2</sup> ) | Coil length (m) |
|-----------------------------|--------------------|----------------------------------------|-----------------|
| <b>CY 1.5 GREEN/YELLOW</b>  | 1.5                | -                                      | 100             |
| <b>CY 2.0 GREEN/YELLOW</b>  | 2.0                | -                                      | 100             |
| <b>CY 3.0 GREEN/YELLOW</b>  | 3.0                | 0.5-0.75                               | 100             |
| <b>CY 4.0 GREEN/YELLOW</b>  | 4.0                | 1.5-2.5                                | 100             |
| <b>CY 5.0 GREEN/YELLOW</b>  | 5.0                | 2.5-4.0                                | 100             |
| <b>CY 6.0 GREEN/YELLOW</b>  | 6.0                | 6.0                                    | 100             |
| <b>CY 8.0 GREEN/YELLOW</b>  | 8.0                | 10.0                                   | 100             |
| <b>CY 10.0 GREEN/YELLOW</b> | 10.0               | 16.0-25.0                              | 100             |
| <b>CY 12.0 GREEN/YELLOW</b> | 12.0               | 35.0                                   | 100             |
| <b>CY 15.0 GREEN/YELLOW</b> | 15.0               | 50.0                                   | 100             |

### Specification.

Material:  
PVC

Operating temperature:  
-20°C to +70°C

Colour:  
Green/Yellow

Insulation resistance:  
1010 Ohm/cm

Dielectric strength:  
20 kV/mm

Elongation at break:  
PVC

Hardness:  
BSS20-30

Flammability:  
Self-Extinguishing in 30 seconds

Approvals:  
BS 2848/3/85T, RoHS compliant