



Coloured PVC sleeveings - coils.

Key features.

- High-grade thin wall PVC sleeving ideal for insulating wire in areas where space is at a premium
- Supplied in continuous 100m coils
- Some sizes are available supplied on reels, please contact us for more information

Part number	Internal dia. (mm)	To cover cable size (mm ²)	Coil length (m)	MOQ (Min order qty)
CY1.0 (Colour)	1.0	-	100	1
CY1.5 (Colour)	1.5	-	100	1
CY2.0 (Colour)	2.0	-	100	1
CY3.0 (Colour)	3.0	0.5 - 0.75	100	1
CY4.0 (Colour)	4.0	1.5 - 2.5	100	1
CY5.0 (Colour)	5.0	2.5 - 4.0	100	1
CY6.0 (Colour)	6.0	6.0	100	1
CY8.0 (Colour)	8.0	10.0	100	1
CY10.0 (Colour)	10.0	16.0 - 25.0	100	1
CY12.0 (Colour)	12.0	35.0	100	1
CY15.0 (Colour)	15.0	50.0	100	500

Specification.

Material:
PVC

Colours available:
Black, blue, brown, green, grey, red, white, yellow

Operating temperature:
-20°C to +70°C

Insulation resistance:
1010 Ohm/cm

Dielectric strength:
20 kV/mm

Elongation at break:
220%

Tensile strength:
15MPa

Hardness:
BSS20-30

Flammability:
Self Extinguishing in 30 seconds

Approvals:
BS 2848/3/85T, RoHS compliant