



This adhesive lined heatshrink, with a medium wall has a 3:1 shrink ratio. It accommodates a wide variety of connector shapes and configurations up to 350mm diameter. Typical applications include strain relief and cable protection, installation cover or jacket repair on low voltage cables, and splice covers for electrical cables.

SPECIFICATION:

MATERIAL: Flame Retardant Polyolefin UL94-V0

COLOUR OPTIONS: Black

OPERATING TEMPERATURE: -55°C to +110°C

SHRINK TEMPERATURE: 120°C

LONGITUDINAL CHANGE: +1% to 10% Max.

DIELECTRICAL STRENGTH: 20kV/mm Min.

THERMAL HEAT AGEING: 168 Hours at 150°C - 500%: Low Temperature Flexibility.

FLAMMABILITY: Fire hazard duration of burning 60s max to ASTM D2671 (jacket only, not including transparent).

CHEMICAL RESISTANCE: Fluid resistance at 23°C for 24 hours for the following fluids: F-54 diesel fluid, H-515 hydraulic fluid, 0-149 lubricating oil.



PART NUMBERS:

PART NO.	COLOUR	MIN. DIA. SUPPLIED (mm)	MAX. DIA. RECOVERED (mm)	RECOVERED WALL THICKNESS (mm)	LENGTH (m)
MW-HSAL10/4	Black	10	4	2.0	1.2
MW-HSAL19/6	Black	19	6	2.0	1.2
MW-HSAL25/8	Black	25	8	2.0	1.2
MW-HSAL28/9	Black	28	9	2.4	1.2
MW-HSAL33/10	Black	33	10	2.4	1.2
MW-HSAL38/12	Black	38	12	2.4	1.2
MW-HSAL43/12	Black	43	12	2.5	1.2
MW-HSAL52/19	Black	52	19	2.5	1.2
MW-HSAL70/25	Black	70	25	2.5	1.2
MW-HSAL90/30	Black	90	30	2.5	1.2
MW-HSAL120/40	Black	120	40	2.7	1.2
MW-HSAL152/48	Black	152	48	3.3	1.2
MW-HSAL170/58	Black	170	58	3.3	1.2
MW-HSAL230/77	Black	230	77	3.3	1.2
MW-HSAL265/85	Black	265	85	3.3	1.2
MW-HSAL300/100	Black	300	100	3.5	1.2
MW-HSAL350/150	Black	350	150	3.5	1.2



CABLECRAFT
creative wiring solutions



Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD.
Phone: 01582 606033 • Fax: 01582 606063 • Email: sales@cablecraft.co.uk • Web: www.cablecraft.co.uk

VAT NO. GB 639 920 900 • CO. REG. NO. 2478297