




SL 2.5/35



SL 4/35



SL 10/35



SL 16/35 N



SL 35/35 N

DESCRIPTION:


The SL range features the proven screw-connection system and a metal clamping foot to secure to the DIN rail, to establish a quick, safe connection for the smallest cross sections. The operating temperature is -40°C to +120°C.

SPECIFICATION:

MATERIAL: Polyamide 6.6 UL 94 - V2

DIN RAIL TYPE: Foot can be snapped on to TS 35 DIN rail

STANDARDS: IEC, UL and CSA approved



PART NUMBERS:

PART NUMBER	COLOUR	CONDUCTOR mm ² /AWG	PACK QUANTITY
SL RANGE TERMINALS			
SL 2.5/35		2.5/22-12	1
SL 4/35		4.0/22-11	1
SL 10/35		10.0/20-6	1
SL 16/35 N		16.0/10-4	1
SL 35/35 N		35.0/12-2	1



Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD.
Phone: 01582 606033 • **Fax:** 01582 606063 • **Email:** sales@cablecraft.co.uk • **Web:** www.cablecraft.co.uk

VAT NO. GB 639 920 900 • CO. REG. NO. 2478297