

DESCRIPTION:

Universal foot, fits symmetrical (top hat) and G rail. Takes 20mm fuse up to 6.3A. Lever lifts to isolate and remove fuse. The operating temperature is -40°C to +120°C.

SPECIFICATION:

MATERIAL: Polyamide 6.6 UL 94 - V2


DIN RAIL TYPE: Foot can be snapped on to TS 35 DIN rail and G rail


STANDARDS: IEC, UL and CSA approved



PART NUMBERS:

RATED VOLTAGE/MAX CURRENT

PART NUMBER	COLOUR	IEC	CONDUCTOR mm ² /AWG	PACK QUANTITY
FUSE DISCONNECT TERMINALS				
STK 2 (COLOUR)	 Beige and Blue	500/6.3	4.0/22-12	1



ACCESSORY TYPE	PART NUMBER	PACK QUANTITY
ACCESSORY FOR FUSE DISCONNECT TERMINALS		
End Plates	AP/SI-2	1



CABLECRAFT™
creative wiring solutions



Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD.
Phone: 01582 606033 • Fax: 01582 606063 • Email: sales@cablecraft.co.uk • Web: www.cablecraft.co.uk

VAT NO. GB 639 920 900 • CO. REG. NO. 2478297