

Dymo® Rhino Pro-5200 Label System



The portable, affordable Rhino 5200 saves you time and money on every job! Press one 'Hot Key' to format text into perfect patch panel labels; press another to print matching cable flags or face plate tags, without retyping!

APPLICATIONS

Ideal for wire and cable, terminal blocks, electrical and patch panels.

KIT CONTENTS

- Dymo® Rhino 5200 printer
- Durable hard carry case
- Rechargeable lithium-ion battery
- 19mm black/white flexible nylon tape
- 12mm black/white vinyl tape
- AC adapter
- Quick reference guide
- User manual on CD-rom

FEATURES

Meets all ANSI and TIA/EIA-606-A industry labelling standards

Exclusive one-touch 'Hot Keys' automatically size, space and format label text for electrical and patch panels, terminal and 110 blocks, wire and cable flags, horizontal and vertical wraps, vertical and fixed length applications.

Prints Code 39 and Code 128 barcodes on 19mm wide labels, ideal for asset management

Uses DYMO® Industrial labels with chemical, heat and UV resistant materials; also prints directly onto heatshrink tubes and non-adhesive labels.

100 label memory for storing commonly used labels.

Dymo® Rhino Pro-5200 label system

Part number	Description
T107-SMS-PRINTER KIT	Dymo® Rhino 5200 kit

Dymo® Rhino tapes

Part number	Colour	For cable dia. (mm)	Width (mm)	Length (m)
Heatshrink tubing				
SMS-TMS-3.9-9	White	1.18 - 2.33	6	1.5
SMS-TMS-3.9-4	Yellow	1.18 - 2.33	6	1.5
SMS-TMS-5.2-9	White	1.73 - 3.73	9	1.5
SMS-TMS-5.2-4	Yellow	1.73 - 3.73	9	1.5
SMS-TMS-7.9-9	White	2.97 - 5.13	12	1.5
SMS-TMS-7.9-4	Yellow	2.97 - 5.13	12	1.5
SMS-TMS-13.2-9	White	4.64 - 8.70	19	1.5
SMS-TMS-13.2-4	Yellow	4.64 - 8.70	19	1.5
Flexible nylon				
SMS-NC-12-4	Yellow	12	--	3.5
SMS-NC-12-9	White	12	--	3.5
SMS-NC-19-9	White	19	--	3.5
Coloured Vinyl				
SMS-V-12-4	Yellow	12	--	5.5
SMS-V-12-9	White	12	--	5.5
SMS-V-19-2	Red	19	--	5.5
SMS-V-19-4	Yellow	19	--	5.5
SMS-V-19-5	Green	19	--	5.5
SMS-V-19-9	White	19	--	5.5
Polyester				
SMS-WP-12-9	White	12	--	5.5
SMS-WP-19-9	White	19	--	5.5
SMS-MP-12-8A	Metalised	12	--	5.5
SMS-MP-19-8A	Metalised	19	--	5.5