




Pre-insulated PVC flanged fork terminals.

Key features.

- Made from oxygen-free high conductivity copper
- Electro-tin plated for excellent conductivity and resistance to corrosion



Specification.

Material:
Electro-tin plated copper

Insulation:
Polyvinyl chloride (PVC)

Max. electrical rating:
■ Red - 19 AMP
■ Blue - 27 AMP
■ Yellow - 48 AMP
 600 Volts - max.
 Max temperature 75°C

Approvals:
 UL Approved E211389, RoHS compliant

Wire Ø mm²	Part no.	Stud size D2 mm	Dimensions (mm)				Pack quantity
			D	Y	B	K	
0.5 - 1.5 Red	CIFF1-3.5	3.5	4.15	16.8	7.5	3.7	100
	CIFF1-4	4	4.15	18.5	7.5	4.3	100
	CIFF1-5	5	4.15	18.5	8.5	5.3	100
	CIFF1-6	6	4.15	21.5	13.5	6.5	100
1.5 - 2.5 Blue	CIFF2-3.5	3.5	4.75	17.8	7.5	3.7	100
	CIFF2-4	4	4.75	19.5	7.5	4.3	100
	CIFF2-5	5	4.75	19.5	8.5	5.3	100
	CIFF2-6	6	4.75	22.5	13.5	6.5	100
4-6 Yellow	CIFF3-3.5	3.5	6.5	23.2	7.6	3.7	50
	CIFF3-4	4	6.5	24.2	7.6	4.3	50
	CIFF3-5	5	6.5	25.6	8.5	5.3	50
	CIFF3-6	6	6.5	28.7	13.5	6.4	50

01582 606033 | sales@cablecraft.co.uk | cablecraft.co.uk

Cablecraft House, Circle Business Centre, Blackburn Road, Houghton Regis, Bedfordshire, LU5 5DD

Registered in England and Wales at 12 Charterhouse Square, London EC1M 6AX | Company registration number 02478297

