



Heavy duty copper tube terminals

Key features.

- Manufactured from seamless Copper Tube to BSEN 12449: 2016
- Fully comply with BS EN 61238-1-2003 and BS 4579
- Ideal for panel building, telecoms and utilities



Specification.

Material:
Seamless Copper Tube to
BSEN 12449: 1999

Approvals:
BS4G 178 Part 2 - 1986
RSE/STD 024 part 7 - issue A
(London Underground Approval)

Service temperature:
Heat resistant up to 240°C

Voltage:
3.3kV

Cable size mm ²	Part no.	Stud size (mm)	Dimensions (mm)								Pack quantity
			A	B	W	E	F	D	L	T	
1.5	CCT1.5-3HD	3	3.6	1.9	5.5	5.0	3.0	7.5	17.0	1.4	1
	CCT1.5-4HD	4	3.6	1.9	6.7	6.0	4.0	7.5	19.5	1.1	1
	CCT1.5-5HD	5	3.6	1.9	7.7	6.5	4.5	7.5	20.4	0.9	1
2.5	CCT2.5-3HD	3	3.9	2.4	5.5	5.0	3.0	7.8	18.0	1.6	1
	CCT2.5-4HD	4	3.9	2.4	6.7	6.0	4.0	7.8	20.0	1.4	1
	CCT2.5-5HD	5	3.9	2.4	7.7	6.9	4.5	7.8	21.2	1.1	1
	CCT2.5-6HD	6	3.9	2.4	9.0	7.5	5.5	7.8	23.0	1.0	1
4	CCT4-4HD	4	4.7	2.8	7.0	6.0	4.0	8.0	20.5	1.7	1
	CCT4-5HD	5	4.7	2.8	8.0	6.4	4.6	8.0	21.5	1.4	1
	CCT4-6HD	6	4.7	2.8	9.0	7.5	5.5	8.0	23.5	1.3	1
6	CCT6-4HD	4	5.9	3.9	8.4	6.1	3.9	10.0	22.5	1.8	1
	CCT6-5HD	5	5.3	3.4	8.0	6.4	4.6	10.0	23.5	1.9	1
	CCT6-6HD	6	5.3	3.4	9.0	7.5	5.5	10.0	25.5	1.7	1
	CCT6-8HD	8	5.3	3.4	11.5	10.0	7.0	10.0	29.5	1.6	1
	CCT6-10HD	10	5.3	3.4	14.5	11.8	7.2	10.0	31.0	0.9	1
10	CCT10-5HD	5	6.9	4.4	10.5	5.9	5.1	9.0	27.0	2.0	1
	CCT10-6HD	6	6.9	4.4	10.5	5.9	5.1	9.0	27.0	2.0	1
	CCT10-8HD	8	6.9	4.4	14.0	9.8	8.3	10.0	35.0	1.6	1
	CCT10-10HD	10	6.9	4.4	16.0	12.0	10.0	10.0	39.0	1.5	1
	CCT10-12HD	12	6.9	4.4	18.0	12.0	10.0	10.0	39.0	1.2	1

Cable size mm ²	Part no.	Stud size (mm)	Dimensions (mm)								Pack quantity
			A	B	W	E	F	D	L	T	
16	CCT16-5HD	5	8.0	5.6	11.0	5.9	5.1	11.0	29.5	2.2	1
	CCT16-6HD	6	8.0	5.6	11.0	5.9	5.1	11.0	29.5	2.2	1
	CCT16-8HD	8	8.0	5.6	14.0	9.8	8.3	11.0	38.0	1.7	1
	CCT16-10HD	10	8.0	5.6	16.0	12.0	10.0	11.0	42.0	1.5	1
	CCT16-12HD	12	8.0	5.6	18.0	12.0	10.0	11.0	42.0	1.3	1
25	CCT25-5HD	5	9.5	7.0	13.5	9.8	8.3	13.0	40.0	2.4	1
	CCT25-6HD	6	9.5	7.0	13.5	9.8	8.3	13.0	40.0	2.4	1
	CCT25-8HD	8	9.5	7.0	13.5	9.8	8.3	13.0	40.0	2.4	1
	CCT25-10HD	10	9.5	7.0	16.0	12.0	10.0	13.0	44.0	2.0	1
	CCT25-12HD	12	9.5	7.0	18.0	12.0	10.0	13.0	44.0	1.8	1
35	CCT35-5HD	5	11.0	8.2	15.5	9.8	8.3	14.0	41.0	2.8	1
	CCT35-6HD	6	11.0	8.2	15.5	9.8	8.3	14.0	41.0	2.8	1
	CCT35-8HD	8	11.0	8.2	15.5	9.8	8.3	14.0	41.0	2.8	1
	CCT35-10HD	10	11.0	8.2	15.5	12.0	10.0	14.0	45.0	2.8	1
	CCT35-12HD	12	11.0	8.2	18.0	12.0	10.0	14.0	45.0	2.2	1
	CCT35-14HD	14	11.0	8.2	20.0	15.0	12.0	14.0	50.0	2.0	1
50	CCT50-5HD	5	12.1	9.5	17.2	9.8	8.3	18.0	46.0	2.4	1
	CCT50-6HD	6	12.1	9.5	17.2	9.8	8.3	18.0	46.0	2.4	1
	CCT50-8HD	8	12.1	9.5	17.2	9.8	8.3	18.0	46.0	2.4	1
	CCT50-10HD	10	12.1	9.5	17.2	12.0	10.0	18.0	50.0	2.4	1
	CCT50-12HD	12	12.1	9.5	17.2	12.0	10.0	18.0	50.0	2.4	1
	CCT50-14HD	14	12.1	9.5	20.0	15.0	12.0	18.0	55.0	1.9	1
	CCT50-16HD	16	12.1	9.5	22.0	15.0	12.0	18.0	55.0	1.7	1
70	CCT70-5HD	5	15.0	11.5	21.2	9.8	8.3	18.0	48.0	3.5	1
	CCT70-6HD	6	15.0	11.5	21.2	9.8	8.3	18.0	48.0	3.5	1
	CCT70-8HD	8	15.0	11.5	21.2	9.8	8.3	18.0	48.0	3.5	1
	CCT70-10HD	10	15.0	11.5	21.2	12.0	10.0	18.0	52.0	3.5	1
	CCT70-12HD	12	15.0	11.5	21.2	12.0	10.0	18.0	52.0	3.5	1
	CCT70-14HD	14	15.0	11.5	21.2	16.5	16.5	18.0	63.0	3.5	1
	CCT70-16HD	16	15.0	11.5	21.2	16.5	16.5	18.0	63.0	3.5	1
95	CCT95-6HD	6	17.0	13.5	24.3	12.0	10.0	24.0	58.0	3.5	1
	CCT95-8HD	8	17.0	13.5	24.3	12.0	10.0	24.0	58.0	3.5	1
	CCT95-10HD	10	17.0	13.5	24.3	12.0	10.0	24.0	58.0	3.5	1
	CCT95-12HD	12	17.0	13.5	24.3	12.0	10.0	24.0	58.0	3.5	1
	CCT95-14HD	14	17.0	13.5	24.3	16.5	16.5	24.0	69.0	3.5	1
	CCT95-16HD	16	17.0	13.5	24.3	16.5	16.5	24.0	69.0	3.5	1

Cable size mm ²	Part no.	Stud size (mm)	Dimensions (mm)								Pack quantity
			A	B	W	E	F	D	L	T	
120	CCT120-8HD	8	19.0	15.0	27.2	16.5	16.5	27.0	73.0	4.0	1
	CCT120-10HD	10	19.0	15.0	27.2	16.5	16.5	27.0	73.0	4.0	1
	CCT120-12HD	12	19.0	15.0	27.2	16.5	16.5	27.0	73.0	4.0	1
	CCT120-14HD	14	19.0	15.0	27.2	16.5	16.5	27.0	73.0	4.0	1
	CCT120-16HD	16	19.0	15.0	27.2	16.5	16.5	27.0	73.0	4.0	1
	CCT120-20HD	20	19.0	15.0	27.2	18.8	14.3	27.0	73.0	4.0	1
150	CCT150-8HD	8	21.0	16.5	30.0	16.5	16.5	27.0	78.0	4.5	1
	CCT150-10HD	10	21.0	16.5	30.0	16.5	16.5	27.0	78.0	4.5	1
	CCT150-12HD	12	21.0	16.5	30.0	16.5	16.5	27.0	78.0	4.5	1
	CCT150-14HD	14	21.0	16.5	30.0	16.5	16.5	27.0	78.0	4.5	1
	CCT150-16HD	16	21.0	16.5	30.0	16.5	16.5	27.0	78.0	4.5	1
	CCT150-20HD	20	21.0	16.5	30.0	18.8	14.3	27.0	78.0	4.5	1
185	CCT185-12HD	12	23.0	18.5	33.5	16.5	16.5	30.0	82.0	4.5	1
	CCT185-14HD	14	23.0	18.5	33.5	16.5	16.5	30.0	82.0	4.5	1
	CCT185-16HD	16	23.0	18.5	33.5	16.5	16.5	30.0	82.0	4.5	1
	CCT185-20HD	20	23.0	18.5	33.5	18.8	14.3	30.0	82.0	4.5	1
240	CCT240-10HD	10	26.0	21.0	37.7	18.0	17.0	32.0	88.0	5.0	1
	CCT240-12HD	12	26.0	21.0	37.7	18.0	17.0	32.0	88.0	5.0	1
	CCT240-14HD	14	26.0	21.0	37.7	18.0	17.0	32.0	88.0	5.0	1
	CCT240-16HD	16	26.0	21.0	37.7	18.0	17.0	32.0	88.0	5.0	1
	CCT240-20HD	20	26.0	21.0	37.7	18.0	17.0	32.0	88.0	5.0	1
300	CCT300-10HD	10	28.0	23.0	18.0	18.0	17.0	37.0	97.0	5.0	1
	CCT300-12HD	12	28.0	23.0	18.0	18.0	17.0	37.0	97.0	5.0	1
	CCT300-14HD	14	28.0	23.0	18.0	18.0	17.0	37.0	97.0	5.0	1
	CCT300-16HD	16	28.0	23.0	18.0	18.0	17.0	37.0	97.0	5.0	1
	CCT300-20HD	20	28.0	23.0	18.0	18.0	17.0	37.0	97.0	5.0	1
400	CCT400-10HD	10	32.0	27.0	47.3	25.0	25.0	38.0	113.0	5.0	1
	CCT400-12HD	12	32.0	27.0	47.3	25.0	25.0	38.0	113.0	5.0	1
	CCT400-14HD	14	32.0	27.0	47.3	25.0	25.0	38.0	113.0	5.0	1
	CCT400-16HD	16	32.0	27.0	47.3	25.0	25.0	38.0	113.0	5.0	1
	CCT400-20HD	20	32.0	27.0	47.3	25.0	25.0	38.0	113.0	5.0	1
500	CCT500HD	ANY	38.1	30.0	55.0	29.0	25.0	44.0	127.0	8.2	1
630	CCT630HD	ANY	44.0	33.8	63.0	25.0	23.0	46.0	127.0	10.2	1
800	CCT800HD	ANY	49.0	38.0	70.0	34.0	34.0	56.0	164.0	11.0	1
1000	CCT1000HD	ANY	53.0	42.5	77.0	34.0	34.0	56.0	169.0	10.5	1