



Uninsulated copper brazed sheet terminals.

Key features.

- For cable sizes from 10mm² - 95mm² and stud sizes from 4mm to 16.0mm
- Maintain strength during the crimping cycle
- Electro tin plated for maximum corrosion resistance and conductivity
- Ideal for panel building, telecoms and utilities
- Maximum electrical rating in AMPs has been tested at a constant working temperature of 50 °C

Specification.

Material:
Electrolytic copper,
electro-tin plated

Maximum temperature:
Heat resistant up to +125°C

Max. elec. rating:
600V - 75°C.
10mm²: 19 AMP, 16mm²: 88 AMP,
25mm²: 115 AMP, 35mm²: 160 AMP,
50mm²: 215 AMP, 70mm²: 235 AMP,
95mm²: 255 AMP

Approvals:
DIN standard 46234

Cable size (mm ²)	Part no.	Stud size D2 (mm)	Max. elec rating (A)	Dimensions (mm)					Pack quantity
				d	y	b	c	ØK	
10	CST10-4	4	70	4.5	16.0	10.0	8.0	4.3	50
	CST10-5	5	70	4.5	16.0	10.0	8.0	5.3	50
	CST10-6	6	70	4.5	17.0	11.0	8.0	6.5	50
	CST10-8	8	70	4.5	20.0	14.0	8.0	8.4	50
	CST10-10	10	70	4.5	21.0	18.0	8.0	10.5	50
	CST10-12	12	70	4.5	23.0	22.0	8.0	13.0	50
16	CST16-5	5	95	5.8	20.0	11.0	10.0	5.3	50
	CST16-6	6	95	5.8	20.0	11.0	10.0	6.5	50
	CST16-8	8	95	5.8	22.0	14.0	10.0	8.4	50
	CST16-10	10	95	5.8	24.0	18.0	10.0	10.5	50
	CST16-12	12	95	5.8	26.0	22.0	10.0	13.0	50

Cable size (mm ²)	Part no.	Stud size D2 (mm)	Max. elec rating (A)	Dimensions (mm)					Pack quantity
				d	y	b	c	ØK	
25	CST25-5	5	125	7.5	25.0	12.0	11.0	5.3	50
	CST25-6	6	125	7.5	25.0	12.0	11.0	6.5	50
	CST25-8	8	125	7.5	25.0	16.0	11.0	8.4	50
	CST25-10	10	125	7.5	26.0	18.0	11.0	10.5	50
	CST25-12	12	125	7.5	31.0	22.0	11.0	13.0	50
	CST25-14	14	125	7.5	31.0	22.0	11.0	15.0	50
	CST25-16	16	125	7.5	35.0	28.0	11.0	17.0	50
35	CST35-6	6	170	9.0	26.0	15.0	12.0	6.5	50
	CST35-8	8	170	9.0	26.0	16.0	12.0	8.4	50
	CST35-10	10	170	9.0	27.0	18.0	12.0	10.5	50
	CST35-12	12	170	9.0	31.0	22.0	12.0	13.0	50
	CST35-14	14	170	9.0	31.0	22.0	12.0	15.0	50
	CST35-16	16	170	9.0	35.0	28.0	12.0	17.0	50
50	CST50-6	6	230	11.0	34.0	18.0	16.0	6.5	50
	CST50-8	8	230	11.0	34.0	18.0	16.0	8.4	50
	CST50-10	10	230	11.0	34.0	18.0	16.0	10.5	50
	CST50-12	12	230	11.0	36.0	22.0	16.0	13.0	50
	CST50-14	14	230	11.0	36.0	22.0	16.0	15.0	50
	CST50-16	16	230	11.0	40.0	22.0	16.0	17.0	50
70	CST70-8	8	265	13.0	38.0	22.0	18.0	8.4	25
	CST70-10	10	265	13.0	38.0	22.0	18.0	10.5	25
	CST70-12	12	265	13.0	38.0	22.0	18.0	13.0	25
	CST70-14	14	265	13.0	38.0	22.0	18.0	15.0	25
	CST70-16	16	265	13.0	42.0	28.0	18.0	17.0	25
95	CST95-10	10	310	15.0	42.0	24.0	20.0	10.5	25
	CST95-12	12	310	15.0	42.0	24.0	20.0	13.0	25
	CST95-14	14	310	15.0	42.0	24.0	20.0	15.0	25
	CST95-16	16	310	15.0	44.0	28.0	20.0	17.0	25