## E/Fact

## THORN

## 96271672 EFACT C2 9L50 SOFT 840 AL FR




## E/Fact

A large square ground recessed luminaire. 9 LED(s) driven at 500mA by integral driver for walkover guidance applications. Body: die-cast aluminium with powdered paint finish. Frame: painted aluminium, 2mm thick. Front glass: frosted toughened sodic glass, 12mm thick, surface temperature complies with EN60598-2-13. Recessing box: polypropylene. Rated IP67, class I electrical. Maximum static load 1000kg. Complete with 4000K LED

Dimensions: 262 x 262 x 200 mm Luminaire input power: 11.5 W Luminaire luminous flux: 115 lm Luminaire efficacy: 10 lm/W Weight: 6.81 kg




TLG\_EFCT\_F\_C2ALFR.jpg



TLG\_EFCT\_M\_2015LD2AL.wmf

Lamp position: STD - standard Light Source: LED Luminaire luminous flux\*: 115 lm Luminaire efficacy\*: 10 lm/W Lamp efficacy: 10 lm/W Colour Rendering Index min.: 80



TLLA\_96271672.ldt

Correlated colour temperature: 4000 Kelvin Rated median useful life\*: 50000h at 25°C Ballast: 1x EL2 Luminaire input power\*: 11.5 W Dimming: FO LOR: 1,00 ULOR: 1,00 DLOR: 0,00

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

In most products the failure of one LED point causes no functional impairment to the lighting performance of the luminaire and is therefore no reason for complaint. Unless otherwise stated all Thorn LED products are suitable for unrestricted use (rated RG1) with regard photobiological blue light safety (IEC/EN60598-1).

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement. © Thorn Lighting