


Round 2m Ducting length Insulated/Uninsulated



Stock Ref	Duct Size	External Dimensions			Resistance (Pa) at flow rate							
		A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
406873	Insulated 100 Ø	200	200	2100	<1	<1	1.7	2.8	3.6	4.5	5.3	6.2
5108250	Uninsulated 100 Ø	100	100	2000	<1	<1	1.7	2.8	3.6	4.5	5.3	6.2
406874	Insulated 125 Ø	225	225	2100	<1	<1	<1	1.3	1.8	2.4	3.1	3.8
434715*	Uninsulated 125 Ø	125	125	1500	<1	<1	<1	1.3	1.8	2.4	3.1	3.8
406875	Insulated 150 Ø	265	265	2100	<1	<1	<1	<1	1.2	1.6	2	2.5
5108248	Uninsulated 150 Ø	150	150	2000	<1	<1	<1	<	1.2	1.6	2	2.5
* 1,5 metres												


* 1.5 metres

Equal Tee Insulated/Uninsulated MMM



Stock Ref	Duct Size	External Dimensions			Resistance (Pa) at flow rate							
		A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
406884	Insulated 100 Ø	290	210	235	vary on installation							
372007	Uninsulated 100 Ø	190	110	135	vary on installation							
406885	Insulated 125 Ø	310	215	260	vary on installation							
428636	Uninsulated 125 Ø	210	115	160	vary on installation							
406886	Insulated 150 Ø	335	245	285	vary on installation							
370237	Uninsulated 150 Ø	235	130	177	vary on installation							

90° Bend Insulated/Uninsulated MM




Stock Ref	Duct Size	External Dimensions			Resistance (Pa) at flow rate							
		A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
406880	Insulated 100 Ø	230	200	200	2.8	5.5	11	20.3	33	45	60	79
372004	Uninsulated 100 Ø	130	100	100	2.8	5.5	11	20.3	33	45	60	79
406881	Insulated 125 Ø	260	230	230	<1	1.8	5	8.2	11.8	18	26	35
427360	Uninsulated 125 Ø	160	130	130	<1	1.8	5	8.2	11.8	18	26	35
406882	Insulated 150 Ø	290	255	255	<1	1.0	2.5	4.1	6.4	9.6	13.5	18
370295	Uninsulated 150 Ø	190	155	155	<1	1.0	2.5	4.1	6.4	9.6	13.5	18

45° Bend Insulated/Uninsulated MM



Stock Ref	Duct Size	External Dimensions			Resistance (Pa) at flow rate								
		A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
406877	Insulated 100 Ø	280	200	230	<1	1.9	8.1	11.7	17.5	24.6	31.4	-	
372005	Uninsulated 100 Ø	180	100	130	<1	1.9	8.1	11.7	17.5	24.6	31.4	-	
406878	Insulated 125 Ø	300	230	250	<1	<1	1.8	2.9	4.6	6.6	9	12.2	
441657	Uninsulated 125 Ø	200	130	150	<1	<1	1.8	2.9	4.6	6.6	9	12.2	

Connector MM



Stock Ref	Duct Size	External Dimensions			Resistance (Pa) at flow rate							
		A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
372006	100 Ø	100	60	-	-	-	-	-	-	-	-	-
428633	125 Ø	125	60	-	-	-	-	-	-	-	-	-
370299	150 Ø	150	60	-	-	-	-	-	-	-	-	-

Reducer



Stock Ref	Duct Size	External Dimensions			Resistance (Pa) at flow rate							
		A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
VA54119	125mm to 100mm	130	57	-	-	-	-	-	-	-	-	-
428632	150mm to 125mm	155	57	-	-	-	-	-	-	-	-	-