

References

SIRCO M

SIRCO M - from 16 to 125 A									
Rating (A) / Frame size	No. of poles	Complete switch body toggle operation	Switch body	Direct handle	Door interlocked external front and right side handle ⁽⁸⁾	External left side handle ⁽⁸⁾	Front external handle for changeover switches ⁽⁸⁾	Shaft for external front and side handle ⁽⁸⁾	4 th pole
16 A / M1	3 P	2205 3000	2200 3000 ⁽¹⁾⁽²⁾⁽³⁾	M00 type Blue 2299 5012 Red 2299 5013	S00 type I - O Black IP55 1471 1111 ⁽⁴⁾ Black IP65 1473 1111 ⁽⁴⁾ Red/Yellow IP65 1474 1111 ⁽⁴⁾	S00 type I - O Black IP65 147A 5111 Red/Yellow IP65 147B 5111	S00 type I - O - II Black IP65 1473 1113 ⁽⁴⁾ I - I+II - II Black IP65 1473 1114 ⁽⁴⁾	S0, S00 type 150 mm 1407 0515 200 mm 1407 0520 320 mm 1407 0532	2200 1000
20 A / M1	3 P	2205 3001	2200 3001 ⁽¹⁾⁽²⁾⁽³⁾						2200 1001
25 A / M1	3 P	2205 3002	2200 3002 ⁽¹⁾⁽²⁾⁽³⁾						2200 1002
32 A / M1	3 P	2205 3003	2200 3003 ⁽¹⁾⁽²⁾⁽³⁾						2200 1003
40 A / M1	3 P	2205 3004	2200 3004 ⁽¹⁾⁽²⁾⁽³⁾						2200 1004
63 A / M2	3 P	2205 3006	2200 3006 ⁽¹⁾⁽²⁾⁽³⁾						2200 1006
80 A / M2	3 P	2205 3008	2200 3008 ⁽¹⁾⁽²⁾⁽³⁾	M01 type Blue 2299 5032	S0 type I - O Black IP55 1481 1111 ⁽⁴⁾ Black IP65 1483 1111 ⁽⁴⁾ Red/Yellow IP65 1484 1111 ⁽⁴⁾	S0 type I - O Black IP65 148A 5111 Red/Yellow IP65 148B 5111	S00 type I - O - II Black IP65 1473 0113 I - I+II - II Black IP65 1473 0		

External operation handle - SIRCO M (continued)

S0 type handle

Rating (A) / Frame size	Type	No. of poles	Operation	Handle colour	External IP	Defeatable handle	Reference
100 ... 125 / M3	Switch	3/4 P	Front and side operation	Black	IP55	yes	1481 1111
	Switch	3/4 P	Front and side operation	Black	IP65	yes	1483 1111
	Switch	3/4 P	Front and side operation	Red/Yellow	IP65	yes	1484 1111
	Switch	3/4 P	Left side	Black	IP65	no	148A 5111
	Switch	3/4 P	Left side	Red/Yellow	IP65	no	148B 5111



access_343_a

S01 type handle

Rating (A) / Frame size	Type	No. of poles	Operation	Handle colour	External IP	Defeatable handle	Reference
16 ... 125 / M1 ... M3	Switch	3/4 P ⁽²⁾	Front and side operation	Black	IP65	yes	1403 2111
	Switch	3/4 P ⁽²⁾	Front and side operation	Red/Yellow	IP65	yes	1404 2111
16 ... 125 / M1 ... M3	Changeover switches I - 0 - II	3/4 P	Front	Black	IP65	yes	1403 2113
	Changeover switches I - 0 - II	3/4 P	Front	Black	IP65	yes	1403 2813⁽¹⁾
	Changeover switches I - I+II - II	3/4 P	Front	Black	IP65	yes	1403 2114
	Changeover switches I - I+II - II	3/4 P	Front	Black	IP65	yes	1403 2814⁽¹⁾

(1) Padlockable in 3 positions.

(2) Can also be used with 6 and 8 pole devices from 16 to 40 A.



S0 handle

S01 handle

access_304_a_1_cat

UL 508 manual motor controller “Suitable as motor disconnect”

References


Rating (A)	No. of poles	Toggle switch (direct handle included)	Rotary switch	Direct handle	External front and right side handles ⁽⁴⁾	Shaft for external handles	Switched fourth pole module	Auxiliary contacts	Terminal shrouds	Door mounting kit
16 A	3 P	2205 3000	2200 3000	Blue 2299 5012	S00 type I - O Black 3R, 12 ⁽¹⁾ 1473 1111	S00 and S0 type 150 mm 5.9 in 1407 0515 200 mm 7.9 in 1407 0520 320 mm 12.6 in 1407 0532 ⁽²⁾	1 P 2200 1000	M type 1 AC NO + NC 2299 0001 1 AC 2 NC 2299 0011	1 P 2294 1005 ⁽³⁾ 3 P 2294 3005 ⁽³⁾	2299 3409
20 A	3 P	2205 3001	2200 3001		Red / Yellow 3R, 12 ⁽¹⁾ 1474 1111		1 P 2200 1001			
25 A	3 P	2205 3002	2200 3002		Black 4, 4X ⁽¹⁾ 147D 1111		1 P 2200 1002			
32 A	3 P	2205 3003	2200 3003		Red / Yellow 4, 4X ⁽¹⁾ 147E 1111		1 P 2200 1003			
40 A	3 P	2205 3004	2200 3004		S0 type I - O Black 1, 3R, 12 ⁽¹⁾ 1483 1111		1 P 2200 1004			
63 A	3 P	2205 3006	2200 3006		Red / Yellow 1, 3R, 12 ⁽¹⁾ 1484 1111		1 P 2200 1006			
80 A	3 P	2205 3008	2200 3008		Black 4, 4X ⁽¹⁾ 148D 1111 Red / Yellow 4, 4X ⁽¹⁾ 148E 1111		1P 2200 1008		1 P 2294 1009 ⁽³⁾ 3 P 2294 3009 ⁽³⁾	

(1) Nema / UL type.

Accessories

Direct operation handle

Rating (A)	Handle color	Handle type	Reference
16 ... 80	Blue	M00	2299 5012



M00 handle

access_277_a_2_cat

External operation handle

Use

The handle locking function prevents the user from opening the door of the enclosure when the switch is in the "ON" position (only if the handle is fitted on the door).

Opening the door when the switch is in the "ON" position is possible by defeating the interlocking function with the use of a tool (authorised persons only). The interlocking function is restored when the door is closed. The handle is padlockable with 3 padlocks.



S00 handle

access_264_a_2_cat



S0 handle

access_279_a_2_cat



S01 handle

access_304_a_2_cat

Front and right side handles I - O

Rating (A)	Handle color	Handle type	Nema / UL type	Standard Reference	Heavy duty Reference
16 ... 80	Black	S00	3R, 12	1473 1111	
16 ... 80	Red / Yellow	S00	3R, 12	1474 1111	
16 ... 80	Black	S00	4, 4X	147D 1111	
16 ... 80	Red / Yellow	S00	4, 4X	147E 1111	
16 ... 80	Black	S0	1, 3R, 12	1483 1111	
16 ... 80	Red / Yellow	S0	1, 3R, 12	1484 1111	
16 ... 80	Black	S0	4, 4X	148D 1111	
16 ... 80	Red / Yellow	S0	4, 4X	148E 1111	