



hoods with single locking lever

- CZV enclosures (without gasket) with monoblock stainless steel lever
- CHV, CMV, CAV and CMAV with stainless steel lever and handle in thermoplastic self-extinguishing material
- the enclosures ensure IP protection rating when mated and locked with the closing levers. To be completed with cable glands.
- UL Type 12 (Nema 12), Type 4 (Nema 4) and Type 4x (Nema 4x) degree of protection according to ANSI/UL 50

ILME
part No.

description

packaging



NEW

Pg and metric threading - top entry - with lever and gasket - IP66 (EN60529)

to be coupled with: hoods with pegs for one lever
covers with pegs for one lever
the enclosures ensure IP69K protection at complete connectors (in compliance with DIN 40050-9)

standard

Pg part No.

Metric part No.

version CZ for CD 15/25, CDD 38, CDA/CDC 10/16, MIXO inserts

CZV 15 LG	size 49.16	- Pg 13,5	MZV 15 LG20	size 49.16	- M20	10
CZV 25 LG	size 66.16	- Pg 16	MZV 25 LG20	size 66.16	- M20	10



standard

Pg part No.

Metric part No.

standard version for JCNE, JCSE, CSH, CNE, CCE, CSE, CD 40/64, CDD, CQE, CMCE 3/6/10, CMSE, CP, CX, MIXO, CME, CMCE/CMCE 12 inserts

CHV 06 LG	size 44.27	- Pg 16	MHV 06 LG25	size 44.27	- M25	10
CHV 10 LG	size 57.27	- Pg 16	MHV 10 LG25	size 57.27	- M25	10
CHV 16 LG	size 77.27	- Pg 21	MHV 16 LG32	size 77.27	- M32	10
CHV 24 LG	size 104.27	- Pg 21	MHV 24 LG32	size 104.27	- M32	10
CHV 32 LG	size 77.62	- Pg 36**	MHV 32 LG40	size 77.62	- M40**	1

insulating version for CME 3/6/10/16 or CMCE 16 inserts

CMV 03 LG	size 57.27	- Pg 16	MMV 03 LG25	size 57.27	- M25	5
CMV 06 LG	size 77.27	- Pg 21	MMV 06 LG32	size 77.27	- M32	5
CMV 16 LG	size 104.27	- Pg 21	MMV 16 LG32	size 104.27	- M32	5

high

Pg part No.

Metric part No.

standard version for JCNE, JCSE, CSH, CNE, CCE, CSE, CD 40/64, CDD, CQE, CMCE 3/6/10, CMSE, CP, CX, MIXO inserts

CAV 06 LG21	size 44.27	- Pg 21**	MAV 06 LG25	size 44.27	- M25**	5
CAV 06 LG29	size 44.27	- Pg 29**	MAV 06 LG32	size 44.27	- M32**	5
CAV 10 LG21	size 57.27	- Pg 21**	MAV 10 LG25	size 57.27	- M25**	5
CAV 10 LG29	size 57.27	- Pg 29**	MAV 10 LG32	size 57.27	- M32**	5
CAV 16 LG21	size 77.27	- Pg 21**	MAV 16 LG25	size 77.27	- M25**	5
CAV 16 LG29	size 77.27	- Pg 29**	MAV 16 LG32	size 77.27	- M32**	5
CAV 24 LG21	size 104.27	- Pg 21**	MAV 24 LG25	size 104.27	- M25**	5
CAV 24 LG29	size 104.27	- Pg 29**	MAV 24 LG32	size 104.27	- M32**	5

insulating version for CME 3/6/10/16 or CMCE 16 inserts

CMAV 03 LG21	size 57.27	- Pg 21	MMAV 03 LG25	size 57.27	- M25	5
CMAV 03 LG29	size 57.27	- Pg 29	MMAV 03 LG32	size 57.27	- M32	5
CMAV 06 LG21	size 77.27	- Pg 21	MMAV 06 LG25	size 77.27	- M25	5
CMAV 06 LG29	size 77.27	- Pg 29	MMAV 06 LG32	size 77.27	- M32	5
CMAV 16 LG21	size 104.27	- Pg 21	MMAV 16 LG25	size 104.27	- M25	5
CMAV 16 LG29	size 104.27	- Pg 29	MMAV 16 LG32	size 104.27	- M32	5

** threaded cable entry with metal adapter. As alternative we can supply this hood with threaded entry, without adapter (use complete cable glands only).


For further information please contact ILME SpA.

hoods from page 83



without entry, to be pierced - with two pegs

to be coupled with: bulkhead or surface mounting housings with lever
hoods with lever
covers with lever
The hoods ensure IP65 or IP66 (EN 60529) and IP69K (DIN 40050-9) by the housing with lever



high

standard version

CAC 06 L	size 44.27	20
----------	------------	----