

BATTENS SPECIFICATION SHEET



Borealis 4ft Twin

4ft Twin, LED Batten

FEATURES

IK rating	IK06
IP rating	IP20
Colour flexibility	Fixed colour
UGR	26
Sensor	Microwave On-Off available
Dimmable	DALI2 and 1-10V available
Input	220-240V 50/60Hz
LED Lifetime	54,000h L70 B10
CRI	>80Ra
SDCM	6
Flicker Free	Yes
Emergency version available	Yes

INSTALLATION INFORMATION

Install Connector Type	Loop in / Loop out
Inrush Current	20A 0,2ms
Construction Material	Steel body, white powder coating PC Opal Diffuser
Weight	1.44Kg
Maximum ambient temperature	-20°C to +40°C
SELV	Yes
Building regulations	Part P
Electric Class (1, 2, 3)	1

PHOTOMETRICS @ 25°C

Product code	Finish	Feature I	Feature II	Feature III	Colour	Beam angle	lm	lm/W	lx @ 1m
BT4TS40	White	40W Non-Dim	No sensor	Non emergency	4000K	120°	5200	130	1354
BT4TS40EM	White	40W Non-Dim	No sensor	Emergency	4000K	120°	5200	130	1354
BT4TM40	White	40W Non-Dim	Microwave sensor	Non emergency	4000K	120°	5200	130	1354
BT4TM40EM	White	40W Non-Dim	Microwave sensor	Emergency	4000K	120°	5200	130	1354
BT4TD40	White	40W DALI2	No sensor	Non emergency	4000K	120°	5200	130	1354
BT4TD40EM	White	40W DALI2	No sensor	Emergency	4000K	120°	5200	130	1354
BT4TV40	White	40W 1-10V	No sensor	Non emergency	4000K	120°	5200	130	1354

ACCESSORIES

BTSK1	Suspension Kit - 2 steel wires, with holders.	Sold Separately
-------	---	-----------------



01604 495 151
collingwoodlighting.com

- /collingwoodlighting
- /collingwoodlighting
- collingwoodled

GUARANTEE / WARRANTY

5 years extended guarantee
2 year guarantee on emergency unit
2 year on-site guarantee

FEATURES & BENEFITS

Multiple fixing points and several wiring options

Highly efficient up to 130lm/W

Microwave built-in, On-Off and dusk-dawn functions, providing energy savings

Flicker-Free, resulting in comfortable and safer working environment

Built in self-test emergency available.
Lumen output in EM mode = 250lm

Ideal for sheds, garages and warehouses

MW sensing range adjustable, up to 4m high, 8m diameter

Diffuser is released by side buttons and easily accessible with loop-in/loop-out screwless terminals reducing installation time

Light source energy efficiency:



Beam angle: 120°

