

13A SWITCHED FUSED  
CONNECTION UNIT

Part Number (2501425374 | NLSQ8313S)



Product Description

A white, square-edged, moulded accessory manufactured in a robust urea construction.

| DESCRIPTION              |                                                                                                         |
|--------------------------|---------------------------------------------------------------------------------------------------------|
| Voltage                  | 240V ~ 50Hz                                                                                             |
| Current Rating           | 13A                                                                                                     |
| Torque Value             | 2.0Nm                                                                                                   |
| Cable Size               | 3x2.5mm² or 2x4.0mm²                                                                                    |
| Double Pole              | Yes                                                                                                     |
| Twin Earth               | Yes                                                                                                     |
| Backbox Depth            | 25mm - 47mm                                                                                             |
| Anti Microbial Certified | Yes                                                                                                     |
| IP Rating                | IP20                                                                                                    |
| Operational Temperature  | -5° to +40°C                                                                                            |
| Standards                | The Low Voltage Directive 2006/95/EC, Modified ISO 22196, BS 1363-4:1995+A4:2012. Fuses to BS 1362:1973 |
| Dimensions               | 86x86x9.5mm (HxWxD)                                                                                     |

| DESCRIPTION          |                                                                 |
|----------------------|-----------------------------------------------------------------|
| Material Composition |                                                                 |
| Front Plate          | Urea                                                            |
| Rear Housing         | Urea                                                            |
| Terminals            | Brass                                                           |
| Earth Strap          | Mild Steel                                                      |
| Terminal Screws      | Steel & Yellow Passivated Silver “on-lay” Copper/Brass Contacts |

Dimensions

