

45A DOUBLE POLE SWITCH

Part Number (2501425348 | NLS8345/2N)

Product Description

A new take on traditional moulded wiring accessories manufactured in bright white Urea.



DESCRIPTION	
Material Composition	
Front Plate	Urea
Terminal Housing	Urea
Terminals	Brass
Internal Mechanism	Formed Press Brass Silver “on-lay” Copper / Brass Contacts
Internal Busbars	Formed Pressed Brass
Earth Strap	Mild Steel
Terminal Screws	Steel & Yellow Passivated

DESCRIPTION	
Voltage	240V~ 50Hz
Current Rating	45A
Torque Value	L+N 2.5Nm, Earth 2.0Nm
Cable Size	2 x 6mm², 1 x 10mm², 1 x 16mm²
Double Pole	Yes
Twin Earth	Yes
Back Box Depth	35-47mm
Anti Microbial Certified	Yes
Neon Indicator	Yes
IP Rating	IP20
Operational Temperature	-5 ° to +40 °C
Standards	EN 60669-1:1999 + A1:2002 + A2:2008 (BS EN 60009-1:2000) BS 4177:1992 + A1:1993, 2:1997, 3:2004, 4:2007 BS 1362-2 : 1995 + A4 : 2002
Dimensions	146x86x9.5mm (HxWxD)

Dimensions

