


FP FIREFIX™ using SPIT Pulsa nailing



CLIP conform fixing requirements of BS5839-1:2002 standard

DESCRIPTION

Pirelli has developed FP Firefix™ in partnership with ITW Construction Products. Pirelli has designed special cable clips and adaptators to fit PULSA 800E.

Pirelli clip is used to fix fire performance cables, holds one or two cables.

PROPERTIES MATERIAL

- Stainless steel
- Available in red or white LSOH powder coating

TOOL

P800E

SIZE SUITABLE

Description	Size	Cable Ø Suitability	Colour	Wire Guide	Box Qty	Code
Firefix™ Single Clip	01	$8,0 \text{ mm}^2 \leq D < 8,2 \text{ mm}^2$	Red	2 core x 1,5 mm ²	500	921622
Firefix™ Double Clip	02	$8,0 \text{ mm}^2 \leq D < 8,5 \text{ mm}^2$	Red	2 core x 1,5 mm ² ou 3 core x 1,0 mm ²	200	921623
Firefix™ Double Clip	04	$8,5 \text{ mm}^2 \leq D < 9,0 \text{ mm}^2$	Red	4 core x 1,0 mm ² ou 3 core x 1,5 mm ²	200	921624
Firefix™ Single Clip	01	$8,0 \text{ mm}^2 \leq D < 8,2 \text{ mm}^2$	White	2 core x 1,5 mm ²	500	924252
Firefix™ Double Clip	02	$8,0 \text{ mm}^2 \leq D < 8,5 \text{ mm}^2$	White	2 core x 1,5 mm ² ou 3 core x 1,0 mm ²	200	924251
Firefix™ Double Clip	04	$8,5 \text{ mm}^2 \leq D < 9,0 \text{ mm}^2$	White	4 core x 1,0 mm ² ou 3 core x 1,5 mm ²	200	924253

PIN SELECTION GUIDE

FP FIREFIX™	C6-20	C6-25	C6-30	HC6-15	HC6-17	HC6-22	HC6-27
Concrete C20/25	●	●					
Concrete C30/37		●			●		
Concrete C40/50				●	●		
Prestressed / Prefabricated concrete				●	●		
Solid brick		●	●				
Hollow brick rendered		●	●				
Hollow concrete block		●	●				
Calcium silicate block		●	●				
Steel				●			

FIXING DENSITY

Recommended maximum spacing of FP FIREFIX™ clips

Cable diameter (mm)	Horizontal spacing (mm)	Vertical spacing (mm)
Not exceeding 15 mm	300	400