



**Fuse-link, low voltage, 60 A, AC 415 V, 33 kA, BS system C type II, 30 x 57 mm, gL/gG, BS**

**EATON**  
Powering Business Worldwide™

**Part no.** 60A 415V AC HOUSE SERVICE  
**Catalog No.** 60LR85

## Delivery program

Product range			Fuse
Basic function			House service fuse-link
Field of application			low voltage
Rated current	I	A	60
Rated voltage			AC 415 V
Construction size			BS system C type II
Size			30 x 57 mm
Utilization category			gL/gG
Breaking Capacity		kA	33
usable for size/applications			protection of incoming cables into residential and commercial properties
Standard/Approval			BS
Shape			cylindrical
Standards/Regulations			BS88-3

## Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013])

Size		Other
Rated voltage	V	415 - 415
Rated voltage		Other
Voltage type		AC
Utilization category		gL/gG (cable protection/equipment protection)
Rated operating frequency	Hz	45 - 62
Nominal current	A	60
With striker		No
Release characteristic		Other
Breaking capacity	kA	33