

PERFECT FOR MULTI-OUTDOOR UTILITY APPLICATIONS

Download IES File from website



**11W LED BULKHEADS**

Robustly constructed, reliable wall fitting offering more discrete illumination for utility applications.


- Tough polycarbonate housing
- Opal diffuser: evenly diffused light output
- Corrosion resistant stainless steel cover fixing screws
- Cable channel on reverse of fitting with 20mm knockout conduit entries
- Hinged diffuser
- 5 year warranty

**BULKLEDPC**

- Integral photocell: automatic dusk to dawn operation

• M.O.M: 1 / O.P.Q: 12

Code	Version	Colour	Wattage	Colour Temp.	Luminaire Lumens	Avg. Rated Life (Hrs)	IP Rating
BULKLED	Standard	Black	11.2W	6500K	900 lm	30,000 hrs	IP65
BULKLEDPC	Photocell						



LED LAMP SPECIFICATIONS:	
Luminaire Lumens (with diffuser)	<b>900 lm</b>
Lumens From Chip (no diffuser)	<b>1400 lm</b>
Rated Wattage	11.2W
Rated luminous flux	900 lm
Nominal life time of the lamp	30,000 hrs
Colour temperature	6500K
Number of switching cycles before premature lamp failure	≥15,000
Warm-up time up to 60 % of the full light output	Instant full light
Dimmable	No
LED array dimensions (L/W)	140 x 130mm
Nominal beam angle	120°
Rated power	11.2W
Rated lamp lifetime	30,000 hrs
Displacement factor	
Lumen maintenance factor at end of nominal life	>80%
Starting time	<0.5s
Colour rendering	≥80
Colour consistency	Within 6 step Macadam ellipse
Rated peak intensity	230cd
Rated beam angle	120°
Voltage	240V
Not suitable for accent lighting	