



Palazzoli
GROUP

CARAVAN HOOK UP UNITS

Fully compliant
with the
18th Edition
Wiring
Regulations



1 Circuit Breaker Access Window:

- Transparent Polycarbonate
- Pad lockable

2 Outlets up to 4 of:

- IEC60309 switched interlocked socket outlets
- 16A or 32A 230V , IP44 or IP67
- Padlockable in on/off position

3 Circuit Protection: Overall Main Switch

- 100A 2P

RCBO:

- 16A / 32A 2P 30mA
- Type B 6KA

Metered versions

- MID certified 45A KWH meters per switched interlocked socket ensure accuracy for consumer billing purposes

4 Enclosure System:

- Techno-polymer
- Weatherproof IP66/IP67
- High resistance to UV rays and chemical agents
- Operating -25 to +50 ° C
- Storage -30 to +70 ° C
- Smooth undrilled walls allow custom cable entry position

5 Modular Construction:

- Flexible enclosure design allows either 16A or 32A switched interlocked socket to be interchanged on the same fixing flange and wire harness
- Allows for upgrade of additional switched interlocked socket easily and quickly at later date

Modular Construction Design Robust Enclosure



Palazzoli
GROUP

16A Single Interlock Version

Mounting Pole



With meter



Without meter



With meter



Without meter



671501

Adapter
Bracket Set
for 4 Interlocks
Version

671504

16A Four Interlocks Version

16A Twin Interlocks Version

32A Single Interlock Version



With meters



Without meters



With meters



Without meters



With meter



Without meter

Part Numbers	Meters	A	Description	Dimensions (HxWxD) mm
665301	1	16	16A, 230V RCBO Protected Single Socket Outlet, Single Width, With Meter	395x122x173
665300	-	16	16A, 230V RCBO Protected Single Socket Outlet, Single Width, Without Meter	395x122x173
665311	1	16	16A, 230V RCBO Protected Single Socket Outlet, With Meter	456x239x173
665310	-	16	16A, 230V RCBO Protected Single Socket Outlet, Without Meter	456x239x173
665322	2	16	16A, 230V RCBO Protected Twin Socket Outlet, With Meter	456x239x173
665320	-	16	16A, 230V RCBO Protected Twin Socket Outlet, Without Meter	456x239x173
665344	4	16	16A, 230V RCBO Protected Four Socket Outlet, With Meter	456x461x173
665340	-	16	16A, 230V RCBO Protected Four Socket Outlet, Without Meter	456x461x173
665411	1	32	32A, 230V RCBO Protected Single Socket Outlet, With Meter	456x239x173
665410	-	32	32A, 230V RCBO Protected Single Socket Outlet, Without Meter	456x239x173

* Available on request : Additional options with switched interlocked socket outlets up to 32A 415V

Conformity to Standards:	EN60947-3	IEC-EN 60309-1	Breaker category:	30 mA B curve 6 kA
		IEC-EN 60309-2	Temperature resistance:	Operating -25 to +50 °C
		IEC-EN 60529		Storage -30 to +70 °C
	BS EN 61009-1	EN 62053-21	Glow wire test:	Sockets 850 °C
	BS 7671:2008	amd 3:2015, 708&709		Enclosures 650 °C
Protection Rating:	IP44	(IP66 on request)	Impact Resistance:	IK08

Meets requirements of BS7671:2018 + Amendment 3:2015, Sections 708 & 709