

Download
IES File from
website



Suspension
pack available

ELESUSPACK
Cable length: 1m

PERFECT FOR SUPERIOR OFFICE
& CORRIDOR APPLICATIONS

5FT LED TWIN SLIMLINE CEILING FITTINGS

A slim, modern design LED ceiling fitting which offers a more stylish alternative to traditional battens. Where a more aesthetically pleasing fixture is desirable this versatile and elegant light source is suitable for commercial, retail and domestic applications.

- Polycarbonate and aluminium construction
- Push terminal connections
- 100 lm / W • 5 year warranty

EMERGENCY VERSION (WITH LDLEM3):

- Pre-wired for easy installation
- LED glows green in standby mode and super bright white light in the event of a mains failure
- Minimum 3 hour functionality in emergency mode
- 118 lumens in emergency mode

- **Fittings:** M.O.M: 1 / O.P.Q: 6
- **ELESUSPACK:** M.O.M: 1 / O.P.Q: 100

Code	Version	Colour	Wattage	Colour Temp.	Luminaire Lumens	Avg. Rated Life (Hrs)	IP Rating
ELEGANCE5	Standard	White	50W	4000K	5000 lm	40,000 hrs	IP20
ELEGAN5EM3	Emergency						
ELESUSPACK	Suspension Pack - Cable Length: 1m						

LED LAMP SPECIFICATIONS:

Luminaire lumens (with diffuser)	5000 lm
Lumens from chip (no diffuser)	5300 lm
Useful lumens	4500 lm
Rated Wattage	50W
Rated luminous flux	4500 lm
Nominal life time of the lamp	40,000 hrs
Colour temperature	4000K
Number of switching cycles before premature lamp failure	15,000
Warm-up time up to 60% of the full light output	<2s
Dimmable	No
Nominal beam angle	120°
Rated power	50W
Rated lamp lifetime	40,000 hrs
Displacement factor	≥0.9
Lumen maintenance factor at end of nominal life	≥0.7
Starting time	<0.5s
Colour rendering	≥80
Colour consistency	Within a six step Macadam ellipse
Rated peak intensity	1353cd
Rated beam angle	120°
Voltage / Frequency	240V~50Hz

Lumen efficacy: 100 lm / W

This product contains a Light Source of Energy Efficiency Class F

Not suitable for accent lighting

