



Flexible Conduit Systems - Metallic



Standard of Compliance
BS EN 61386-1:2008

- Specifications**
- -30°C to +300°C
 - Non-flammable
 - Compression class 4 (1250N)
 - Impact class 4 (6 Joules)
 - Highly flexible
 - High mechanical strength

Galvanised Steel - Self Coloured

List No.	Size Nominal	Length	Pack Qty
SPRG1650	16mm	50m	1
SPRG2010	20mm	10m	1
SPRG2050	20mm	50m	1
SPRG2510	25mm	10m	1
SPRG2550	25mm	50m	1



Standard of Compliance
BS EN 61386-1:2008

- Specifications**
- -15°C to +70°C
 - Self Extinguishing
 - Compression class 4 (1250N)
 - Impact class 4 (6 Joules)
 - Highly flexible
 - High mechanical strength

Liquid Resistant PVC Covered Steel - Black

List No.	Size Nominal	Length	Pack Qty
SPRP1250B	12mm	50m	1
SPRP1610B	16mm	10m	1
SPRP1650B	16mm	50m	1
SPRP2010B	20mm	10m	1
SPRP2050B	20mm	50m	1
SPRP2510B	25mm	10m	1
SPRP2550B	25mm	50m	1
SPRP3210B	32mm	10m	1
SPRP3230B	32mm	30m	1
SPRP4010B	40mm	10m	1
SPRP4030B	40mm	30m	1
SPRP5010B	50mm	10m	1
SPRP5030B	50mm	30m	1



Standard of Compliance
BS EN 61386-1:2008

- Specifications**
- -20°C to +80°C
 - Low Smoke - Zero Halogen
 - Compression class 4 (250N)
 - Impact class 4 (6 Joules)
 - Highly flexible
 - High mechanical strength
 - Flame Retardant - Self Extinguishing

Liquid Resistant Polyolefin Covered Steel

List No.	Size Nominal	Length	Pack Qty
LFH2030B	20mm	30m	1



- Specifications**
- IP54 when used with PVC or Polyolefin coated conduits

Male Fixed Straight Connector - Brass

List No.	Size Nominal	Pack Qty
MFG1216	12mm x M16	10
MFG1616	16mm x M16	10
MFG1620	16mm x M20	10
MFG2020	20mm x M20	10
MFG2525	25mm x M25	10
MFG3232	32mm x M32	1
MFG4040	40mm x M40	1
MFG5050	50mm x M50	1



- Specifications**
- IP54 when used with PVC or Polyolefin coated conduits

Male Swivel Straight Connector - Brass

List No.	Size Nominal	Pack Qty
MSG1216	12mm x M16	10
MSG1616	16mm x M16	10
MSG1620	16mm x M20	10
MSG2020	20mm x M20	10
MSG2525	25mm x M25	10
MSG3232	32mm x M32	1
MSG4040	40mm x M40	1
MSG5050	50mm x M50	1