TECHNICAL DATA
FLEX 240

PRODUCT CODE

SL-240

GAP lighting
Smart LED Solutions

PRODUCT DESCRIPTION

FLEX 240 is a durable direct to mains LED striplight with sealed enclosure for anti UV protection.
Ideal for projects which require long run installations and where there are space limitations for power supplies.

Accessories

Joining clip	Power lead	End cap	SL-240CLIP

PRODUCT FEATURES

240v LED strip with flexible PCB

No power supply required

Maximum run length 100m

Cutting points per 500mm

Bespoke cutting service available

Super bright output

Sealed rubber enclosure

Suitable for interior and exterior applications

Ideal for large commercial projects

PRODUCT DATA

Model	SL-240
LED Brand	Epistar SMD 5050 (60 per metre)
Power	10W p/m
Luminous Flux	1080Lm
CRI	>80
Protection	IP65
Colour	Blue | WW - 3000k | W - 6000k | CW - 4000k
Input	240V
Material	PVC
Beam Angle	120°
Life	>30,000 hours
Dimensions	W 14mm | H 7mm
Approvals	CE | ROHS

CONTROL OPTIONS

T-6Z-240 (for on-off & dimming)
T-CON240 (DMX option available)

INSTALLATION

SL-240KIT required - includes joining clip, power lead and end cap
Fixing clips SL-240CLIPS or aluminium channel PROFILE240 recommended

WIRING

240V Direct to mains

Unit 14-15 Schooner Court | Crossways Business Park | Kent | DA2 6NW
Tel. +44 (0) 1322 620 100 | Email. info@gaplighting.co.uk
www.gaplighting.co.uk