

Technical Data Sheet


Holesaw Accessories

Description	Suitable for size	Shank	Thread	Grub Screw	Part No.
9.5mm Hex Shank Drive Arbor	14-29mm	9.5mm Hex	1/2" - 20 (U.N.F)	M8x6	CHD16-29HEX
SDS Plus Shank Drive Arbor	14-29mm	SDS Plus	1/2" - 20 (U.N.F)	M8x6	CHD16-29SDS
13mm Hex Shank Drive Arbor	32-152mm	13mm Hex	5/7" - 18 (U.N.F)	M8x14	CHD32-64HEX
SDS Plus Shank Drive Arbor	32-152mm	SDS Plus	5/8" - 18 (U.N.F)	M8x14	CHD32-64SDS




HOLESAW ASSEMBLY


Holesaw Assembly Guide Below for fitting adaptors to holesaws sized 32mm+



Take the adaptor and turn the knurled ring anti-clockwise to retract the drive pins into the position shown.
Screw the desired holesaw onto the adaptor until its finger tight.



On the back plate of the holesaw are 4 drive pin location holes situated around the adaptor screw thread hole. The hole saw should be 'backed off' until the first pair of drive pin location holes line up with the adaptor drive pins.



Screw the knurled ring clockwise to locate adaptor drive pins into the holes on the back of the holesaw. Notice the gap between the holesaw and the adaptor. This is necessary to prevent the holesaw locking onto the adaptor during the drilling process.

